



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 93357**93357 – CMH250/U/830/R**


GE ConstantColor® Chromafit™ CMH® Ceramic Metal Halide T15

This lamp can be used as a retrofit for 250W high pressure sodium lamps.

RoHS Compliant

[Print this Page](#)
[Convert to PDF](#)
GENERAL CHARACTERISTICS

Lamp type	High Intensity Discharge - Ceramic Metal Halide
Bulb	T15
Base	Mogul Screw (E39)
Bulb Finish	Clear
Wattage	250
Rated Life	24000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Enclosed fixtures only
LEED-EB MR Credit	40 picograms Hg per mean lumen hour



Bulb



Base

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	25000
Mean Lumens	20000
Nominal Initial Lumens per Watt	100
Color Temperature	3000 K
Color Rendering Index (CRI)	85

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Warm Up Time to 90%	2 min
Warm Up Time to 90% (MIN)	2 min
Warm Up Time to 90% (MAX)	5 min
Hot Restart Time to 90% (MIN)	10 min
Hot Restart Time to 90% (MAX)	15 min

DIMENSIONS

Maximum Overall Length (MOL)	9 3/4
Light Center Length (LCL)	5 3/4

PRODUCT INFORMATION**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)**Brochures**

Application/Segment Brochures

- [Contractor Lighting](#)

Product Brochures

- [Ceramic Metal Halide](#)

[MSDS \(Material Safety Data Sheets\)](#)[Disposal Policies & Recycling Information](#)

Product Code	93357
Description	CMH250/U/830/R
ANSI Code	M168/S50
Standard Package	Case
Standard Package GTIN	10043168933572
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168933575

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
87214	GES250ML5AC4-5	1	0.9	1.0
71706	GES250ML5AC4-55	1	0.9	1.0
87121	GES250MLTAC4-5	1	0.9	1.0

CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

[See list of cautions & warnings.](#)

NOTES

- Rated life based on 11 hours per start
- Use electronic ballast, peak lead ballast, or system which can shut itself off if ballast overheating occurs

[Return To Top](#)