




GE  
Lighting

### 31068 - CMH150CU942MED/O

GE Protected ConstantColor® PulseArc® CMH® Ceramic Metal Halide ED17

a product of  
ecomagination



#### CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

##### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use excessive force when installing lamp.
  - Do not use lamp if outer glass is scratched or broken.

##### Warning

- A damaged lamp emits UV radiation which may cause eye/skin injury
  - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Do not turn on lamp until fully installed.
- Risk of Electric Shock
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Turn power off before inspection, installation or removal.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Do not exceed rated voltage.
  - Do not store flammable materials near/below lamp.
  - Do not turn on lamp until fully installed.
  - Do not use beyond rated life.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Operate lamp only in specified position.
  - Use only properly rated ballast.

#### GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Ceramic Metal Halide ED17
Bulb	ED17
Base	Medium Screw (E26)
Bulb Finish	Coated
Wattage	150
Rated Life	15000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Bulb Temperature (MIN)	190 °C
Bulb Temperature (MAX)	400 °C
LEED-EB MR Credit	72 picograms Hg per mean lumen hour

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	11000
Mean Lumens	8300
Nominal Initial Lumens per Watt	73
Color Temperature	4200 K
Color Rendering Index (CRI)	90

#### ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Warm Up Time to 90% (MIN)	2 min
Warm Up Time to 90% (MAX)	5 min
Hot Restart Time to 90%	15 min
Hot Restart Time to 90% (MAX)	15 min

#### DIMENSIONS

Maximum Overall Length (MOL)	5.43 cm
Nominal Length	5.43 cm
Bulb Diameter (DIA)	2.125 cm
Bulb Diameter (DIA) (MAX)	2.125 cm
Light Center Length (LCL)	3.37 cm

#### PRODUCT INFORMATION

Product Code	31068
Description	CMH150CU942MED/O
ANSI Code	C102/M102/M142
Standard Package	Case
Standard Package GTIN	10043168310687
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168310680