



Commercial Products & Solutions



 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > [High Intensity Discharge](#) > [Ceramic Metal Halide](#) > [PAR](#) > [PAR20](#) > 42069
42069 – CMH39UPAR20SP10

GE ConstantColor® PulseArc® CMH® Ceramic Metal Halide PAR20

[Print this Page](#)
[Convert to PDF](#)

 a product of
ecomagination
GENERAL CHARACTERISTICS

Lamp type	High Intensity Discharge - Ceramic Metal Halide
Bulb	PAR20
Base	Medium Screw (E26)
Wattage	39
Rated Life	10000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
LEED-EB MR Credit	238 picograms Hg per mean lumen hour
Additional Info	Ballast thermal protection, UV control

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	2100
Nominal Initial Lumens per Watt	53
Beam Spread	10 °
Center Beam Candlepower (CBCP)	22000
Color Temperature	3000 K
Color Rendering Index (CRI)	86

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Open Circuit Voltage (peak lead ballast) (MIN)	280 V
Open Circuit Voltage (RMS lag ballast) (MIN)	198 V
Warm Up Time to 90% (MAX)	2 min/3 min
Hot Restart Time to 90% (MIN)	10 min
Hot Restart Time to 90% (MAX)	15 min

DIMENSIONS

Maximum Overall	3.6000
-----------------	--------

ADDITIONAL RESOURCES[Catalogs](#)[Testimonials](#)**Brochures**

Product Brochures

- [HID Lamps](#)
 - [Color](#)
 - [Ceramic Metal Halide](#)
- Application/Segment Brochures
- [Contractor Lighting](#)

Sell Sheets

- [GE ConstantColor® CMH® Lamps](#)

[IES/Photometric Download](#)[MSDS \(Material Safety Data Sheets\)](#)[Disposal Policies & Recycling Information](#)

Length (MOL)	
Nominal Length	3 1/2
Bulb Diameter (DIA)	2 1/2

PRODUCT INFORMATION

Product Code	42069
Description	CMH39UPAR20SP10
ANSI Code	M130
Standard Package	Case
Standard Package GTIN	10043168420690
Standard Package Quantity	15
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
UPC	043168420693

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
74116	GEMH39-MC-120	1	0.99	1.0
75378	GEMH39-MCM-120	1	0.99	1.0
87501	GEMH39-MSF-120	1	0.99	1.0

 CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information:

<http://www.fda.gov/cdrh/radhealth/products/urburns.html>

[See list of cautions & warnings.](#)

NOTES

- Rated life based on 11 hours per start
- Use electronic ballast, peak lead ballast, or system which can shut itself off if ballast overheating occurs

[Return To Top](#)