





GE
Lighting

20575 - 240 PAR 56 VNSP

GE PAR56 - Very Narrow Spot



CAUTIONS & WARNINGS

Warning

- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Use in enclosed fixture rated for this product.
 - Avoid direct water/liquid contact.

NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Screw Terminals
Filament	C-6
Wattage	240
Voltage	12
Rated Life	2000 hrs
Primary Application	Very Narrow Spot

PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal	7.0 - 10.0 °/9.0 - 50.0 °
Beam Spread - Vertical	10.0 - 10.0 °/6.0 - 50.0 °
Center Beam Candlepower (CBCP)	140000
Color Temperature	2800 K

DIMENSIONS

Maximum Overall Length (MOL)	4.5000 in(114.3 mm)
Bulb Diameter (DIA)	7.000 in(177.8 mm)
Bulb Diameter (DIA) (MAX)	7.000 in(177.8 mm)

PRODUCT INFORMATION

Product Code	20575
Description	240 PAR 56 VNSP
Standard Package	Case
Standard Package GTIN	10043168205754
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168205757