



GE
Lighting

41433 - MPR1000/VBU/HO/O

GE Protected Multi-Vapor® Quartz Metal Halide BT56

CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

- Lamp may shatter and cause injury if broken
 - Dispose of lamp in a closed container.
 - Do not use excessive force when installing lamp.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- A damaged lamp emits UV radiation which may cause eye/skin injury
 - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Electric Shock
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not store flammable materials near/below lamp.
 - Do not turn on lamp until fully installed.
 - Do not use beyond rated life.
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - If used on a dimming system, see instructions.
 - Operate lamp only in specified position.
 - Turn lamp off at least once for 15 minutes per week.
 - Use only properly rated ballast.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.

GRAPHS & CHARTS

Spectral Power Distribution

GENERAL CHARACTERISTICS

| | |
|---------------------------|--|
| Lamp Type | High Intensity Discharge - Quartz Metal Halide |
| Bulb | BT56 |
| Base | Mogul Screw (EX39) |
| Bulb Finish | Clear |
| Wattage | 1000 |
| Rated Life | 12000 hrs |
| Bulb Material | Hard glass |
| Lamp Enclosure Type (LET) | Open or enclosed fixtures |
| LEED-EB MR Credit | 136 picograms Hg per mean lumen hour |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------|--------|
| Initial Lumens | 110000 |
| Mean Lumens | 88500 |
| Nominal Initial Lumens per Watt | 110 |
| Color Temperature | 3500 K |
| Color Rendering Index (CRI) | 65 |

ELECTRICAL CHARACTERISTICS

| | |
|-------------------------------|-----------------------|
| Burn Position | Vertical base up ±15° |
| Warm Up Time to 90% (MIN) | 2 min |
| Warm Up Time to 90% (MAX) | 5 min |
| Hot Restart Time to 90% (MIN) | 10 min |
| Hot Restart Time to 90% (MAX) | 15 min |

DIMENSIONS

| | |
|------------------------------|----------|
| Maximum Overall Length (MOL) | 15.37 cm |
| Nominal Length | 15.37 cm |
| Bulb Diameter (DIA) | 7 cm |
| Bulb Diameter (DIA) (MAX) | 7 cm |
| Light Center Length (LCL) | 9.5 cm |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------|
| Product Code | 41433 |
| Description | MPR1000/VBU/HO/O |
| ANSI Code | M47 |
| Standard Package | Case |
| Standard Package GTIN | 10043168414330 |
| Standard Package Quantity | 6 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 6 |
| UPC | 043168414333 |