

71630 - F54T5/850/WM/ECO

GE Ecolux® Watt-Miser® Starcoat® T5

- Saves energy compared to standard wattage lamps
- Passes TCLP, which can lower disposal costs.

Photo
Not Available

Rendering

High Color



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight
Bulb	T5
Base	Miniature Bi-Pin (G5)
Rated Life	30000.0 hrs
Rated Life (rapid start) @ Time	30000.0 @ 3.0/36000.0 @ 12.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	-20.0 °C
LEED-EB MR Credit	19 picograms Hg per mean lumen hour
Additional Info	Dimmable with appropriate dimming ballast./TCLP compliant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	4790.0
Mean Lumens	4410.0
Nominal Initial Lumens per Watt	93
Color Temperature	5000.0 K
Color Rendering Index (CRI)	85.0
S/P Ratio (Scotopic/Photopic Ratio)	1.9

ELECTRICAL CHARACTERISTICS







Wattage	51.0
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	45.8000 in(1163.3 mm)
Nominal Length	45.200 in(1148.1 mm)
Bulb Diameter (DIA) (MAX)	0.670 in(17.0 mm)
Bulb Diameter (DIA)	0.625 in(15.9 mm)
Max Base Face to Base Face (A)	45.240 in(1149.1 mm)
Face to End of Opposing Pin (B) (MIN)	45.420 in(1153.7 mm)
Face to End of Opposing Pin (B) (MAX)	45.520 in(1156.2 mm)

PRODUCT INFORMATION

Product Code	71630
Description	F54T5/850/WM/ECO
Standard Package	Case
Standard Package GTIN	10043168716304
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168716307



GRAPHS & CHARTS
Graphs_Spectral Power Distribution

