

Presented By: 1000Bulbs.com
Contact Phone:
Contact E-mail:

Customer Name:
Project Name:
Fixture Type:



GE
Lighting



15776 - F20T12CIN55HOCVG

GE covRguard® Showbiz® T12 - Stage & Studio; Shatter-Resistant

• Film friendly full spectrum lamp designed to meet the spectral matching of today's daylight or tungsten film stock. High CRI 90+ with no expensive gell required.



High Color Rendering



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.

NOTES

- Cinema55 lamps are 5500K daylight, chromaticity x=.325 y=.321, CRI 96, Blue bases
- Light Balancing LB index: mired shift value limit is ± 5 . Color compensating CC filter value limit $\pm 5m$. CC filter density: + magenta, - green. The LB and CC limits are specified to eliminate the need to add external color adjusting filters in cinematographic lighting.

GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight Linear
Bulb	T12
Base	Medium Bi-Pin (G13)
Rated Life	7500.0 hrs
Bulb Material	Soda lime
LEED-EB MR Credit	3463 picograms Hg per mean lumen hour
Primary Application	Stage & Studio; Shatter-Resistant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	1100.0
Mean Lumens	770.0
Nominal Initial Lumens per Watt	31
Color Temperature	5500.0 K
CIE Color x	0.33
CIE Color y	0.335
Color Rendering Index (CRI)	96.0

ELECTRICAL CHARACTERISTICS

Wattage	35.0
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	24.0000 in(609.6 mm)
Bulb Diameter (DIA)	1.500 in(38.1 mm)

PRODUCT INFORMATION

Product Code	15776
Description	F20T12CIN55HOCVG
Standard Package	Case
Standard Package GTIN	10043168157763
Standard Package Quantity	24
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168157766