





GE  
Lighting

## 20138 - 200PAR46/3MFL12P

GE PAR46 - Medium Flood



### CAUTIONS & WARNINGS

#### Warning

- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Use in enclosed fixture rated for this product.
  - Avoid direct water/liquid contact.
- Risk of Fire
  - Keep combustible materials away from lamp.

#### NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

### GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR46
Base	Medium Side Prong
Filament	CC-13
Rated Life	2000.0 hrs
Primary Application	Medium Flood

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2270.0
Beam Spread - Horizontal	40.0 - 10.0 °/27.0 - 50.0 °
Beam Spread - Vertical	24.0 - 10.0 °/13.0 - 50.0 °
Center Beam Candlepower (CBCP)	11500.0
Color Temperature	2750.0 K
Nominal Initial Lumens per Watt	11

### ELECTRICAL CHARACTERISTICS

Wattage	200.0
Voltage	120.0

### DIMENSIONS

Maximum Overall Length (MOL)	4.0000 in(101.6 mm)
Bulb Diameter (DIA)	5.750 in(146.0 mm)

### PRODUCT INFORMATION

Product Code	20138
Description	200PAR46/3MFL12P
Standard Package	Case
Standard Package GTIN	10043168201381
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168201384