





GE  
Lighting

**43703 - Q300T3/CL-6PK**

GE Quartzline® T2.5 - Stage & Studio



**CAUTIONS & WARNINGS**

**Caution**

- Lamp emits UV radiation which may cause eye/skin irritation. RG-1
  - Minimize exposure.
- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

**Warning**

- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Turn power off before installing lamp.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Pressurized lamp—unexpected rupture may cause injury, fire, or property damage
  - Do not exceed 110% of rated voltage.
  - Do not touch glass with bare hands.
  - Do not use lamp if outer glass is scratched or broken.
  - Operate lamp only in specified position – see instructions.
  - Use eye protection when handling lamp.
  - Use in enclosed fixture rated for this product.

**GENERAL CHARACTERISTICS**

Lamp Type	Halogen - Double-Ended
Bulb	T2.5
Base	Recessed Single Contact (R7s)
Filament	C-8
Bulb Finish	Clear
Rated Life	2000.0 hrs
Primary Application	Stage & Studio

**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	5950.0
Color Temperature	2950.0 K
Nominal Initial Lumens per Watt	19

**ELECTRICAL CHARACTERISTICS**

Wattage	300.0
Voltage	120.0
Burn Position	Horizontal

**DIMENSIONS**

Maximum Overall Length (MOL)	4.6880 in(119.1 mm)
Bulb Diameter (DIA)	0.312 in(7.9 mm)
Light Center Length (LCL)	2.250 in(57.2 mm)

**PRODUCT INFORMATION**

Product Code	43703
Description	Q300T3/CL-6PK
ANSI Code	EHM
Standard Package	Master
Standard Package GTIN	10043168437032
Standard Package Quantity	144
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	144
UPC	043168437035