


Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	†Wattage Equivalency	*Rated Life - Hours L70	Dimmable	†ENERGY STAR®	‡Location Rating	Additional Information
Directional Lamps (PAR) (continued)																	
Commercial PAR38 (Indoor/Outdoor) (continued) (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)																	
	MED	12	66116	LED12DP38S827/35	120	6	5.31	660	1500	2700	82	65W	25,000	▲	★	Damp	Flood, 35° beam, Silver, 65-w Repl.
		12	90150	LED12DP382W83025	120	6	5.12	950	4400	3000	84	85W	25,000	▲	★	Wet	Narrow Flood, 25° beam, White
		12	90151	LED12DP382W83035	120	6	5.12	950	2700	3000	84	85W	25,000	▲	★	Wet	Flood, 35° beam, White
		12	90132	LED12DP382W82725	120	6	5.12	850	4000	2700	84	85W	25,000	▲	★	Wet	Narrow Flood, 25° beam, White
		12	90133	LED12DP382W82735	120	6	5.12	850	2500	2700	84	85W	25,000	▲	★	Wet	Flood, 35° beam, White
		12	89990	LED12DP382WFL/TP	120	3	5.12	950	2700	3000	84	85W	25,000	▲	★	Wet	Flood, 35° beam, White
		18	90159	LED18DP38W830/25	120	6	5.12	1300	7600	3000	84	100W	25,000	▲	★	Wet	Narrow Flood, 25° beam, White
		18	90160	LED18DP38W830/40	120	6	5.12	1300	2400	3000	84	100W	25,000	▲	★	Wet	Flood, 40° beam, White
		18	90154	LED18DP38W827/25	120	6	5.12	1200	7000	2700	84	100W	25,000	▲	★	Wet	Narrow Flood, 25° beam, White
		18	94453	LED18DP38W827/40	120	6	5.12	1200	2200	2700	84	100W	25,000	▲	★	Wet	Flood, 40° beam, White
		18	90162	LED18DP38W840/25	120	6	5.12	1400	8200	4000	84	100W	25,000	▲	★	Wet	Narrow Flood, 25° beam, White
		18	90163	LED18DP38W840/40	120	6	5.12	1400	2600	4000	84	100W	25,000	▲	★	Wet	Flood, 40° beam, White
		18	89992	LED18DP38W/FL/TP	120	6	5.12	1300	2400	3000	84	100W	25,000	▲	★	Wet	Flood, 40° beam, White
		18	22235	LED18DP38FL5K/TP	120	3	5.12	1500	3200	5000	84	100W	25,000	▲	★	Wet	Flood, 40° beam, White
		20	64828	LED20DP38S827/15	120	6	5.31	1000	8500	2700	80	90W	50,000	▲	★	Wet	Spot, 15° beam, Silver, 90-w Repl.
		20	65847	LED20DP38/FL/TP	120	3	5.31	1000	1700	2700	80	95W	25,000	▲	★	Wet	Flood, 40° beam, Silver, 95-w Repl.
		20	66326	LED20DP38S840/15	120	6	5.31	1250	10000	4000	80	100W	25,000	▲	★	Wet	Spot, 15° beam, Silver, 100-w Repl.
		20	68202	LED20DP38V840/40	120	6	5.1	1200	2300	4000	82	100W	25000	▲	★	Wet	Flood, 40° beam, Silver, 100-w Repl.
		20	68194	LED20DP38V830/12	120	6	5.1	1100	15500	3000	82	100W	25000	▲	★	Wet	Spot, 12° beam, Silver, 100-w Repl.
		20	68195	LED20DP38V830/25	120	6	5.1	1100	5100	3000	82	100W	25000	▲	★	Wet	Narrow Flood, 25° beam, Silver, 100-w Repl.
		20	68196	LED20DP38V830/40	120	6	5.1	1100	2100	3000	82	90W	25000	▲	★	Wet	Flood, 40° beam, Silver, 90-w Repl.
		20	68197	LED20DP38V827/12	120	6	5.1	1000	14000	2700	82	100W	25000	▲	★	Wet	Spot, 12° beam, Silver, 100-w Repl.
		20	68198	LED20DP38V827/25	120	6	5.1	1000	4900	2700	82	90W	25000	▲	★	Wet	Narrow Flood, 25° beam, Silver, 90-w Repl.
		20	68199	LED20DP38V827/40	120	6	5.1	1000	1900	2700	82	90W	25000	▲	★	Wet	Flood, 40° beam, Silver, 90-w Repl.
		20	68204	LED20DP38V/FL/TP	120	3	5.1	1000	1900	2700	82	90W	25000	▲	★	Wet	Flood, 40° beam, Silver, 90-w Repl.
		20	68200	LED20DP38V840/12	120	6	5.1	1200	17000	4000	82	100W	25000	▲	★	Wet	Spot, 12° beam, Silver, 100-w Repl.
20	68201	LED20DP38V840/25	120	6	5.1	1200	5300	4000	82	100W	25000	▲	★	Wet	Narrow Flood, 25° beam, Silver, 100-w Repl.		
26	68183	LED26DP38S830/12	120	6	5.31	1500	24000	3000	82	130W	50,000	▲	★	Wet	Spot, 12° beam, Silver, 130-w Repl.		
26	68184	LED26DP38S830/25	120	6	5.31	1500	6800	3000	82	130W	50,000	▲	★	Wet	Narrow Flood, 25° beam, Silver, 130-w Repl.		
26	68185	LED26DP38S830/40	120	6	5.31	1500	3100	3000	82	120W	50,000	▲	★	Wet	Flood, 40° beam, Silver, 120-w Repl.		
26	68182	LED26DP38S840/40	120	6	5.31	1650	3200	4000	82	120W	50,000	▲	★	Wet	Flood, 40° beam, Silver, 120-w Repl.		
26	68181	LED26DP38S-FL/TP	120	6	5.31	1650	3200	4000	82	120W	50,000	▲	★	Wet	Flood, 40° beam, Silver, 120-w Repl.		

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70).

** Minimum order quantity = 6

† Incandescent or halogen wattage equivalencies based on Energy Star guidelines using lumens or CBCP according to lamp type

‡ Energy Star status: Certified as meeting Energy Star guidelines.

§ UL 1993 Environmental Requirements for LED Lamps, see page 6-2.

Note: Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

For the most up-to-date product information, see www.gelighting.com. To convert inches to millimeters, multiply by 25.4. All footnote references found at the end of this section.

Incandescent

Halogen

High Intensity Discharge

Fluorescent

Compact Fluorescent

LED Lamps and Systems

Stage and Studio

Miniature, Sealed Beam and Automotive

Projection