




LED Lamps and Systems

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	†Wattage Equivalency	*Rated Life - Hours L70	Dimmable	††ENERGY STAR®	‡Location Rating	Additional Information
Directional Lamps (PAR) (continued)																	
Compact PAR20 (50-watt halogen replacements – based on ENERGY STAR® requirements for center beam candlepower)																	
	MED	7	61915	LED7DP20B830/12	120	6	3.55	330	3400	3000	81	50W	50,000	▲	★	Damp	Accent, 12° beam, Black
		7	61916	LED7DP20B830/20	120	6	3.55	330	2070	3000	80	50W	50,000	▲	★	Damp	Accent, 20° beam, Black
		7	61917	LED7DP20B827/20	120	6	3.55	300	1900	2700	80	50W	50,000	▲	★	Damp	Accent, 20° beam, Black
		7	61918	LED7DP20W830/12	120	6	3.55	330	3400	3000	81	50W	50,000	▲	★	Damp	Accent, 12° beam, White
		7	61919	LED7DP20W830/20	120	6	3.55	330	2070	3000	80	50W	50,000	▲	★	Damp	Accent, 20° beam, White
		7	61920	LED7DP20W827/20	120	6	3.55	300	1900	2700	80	50W	50,000	▲	★	Damp	Accent, 20° beam, White
		7	61921	LED7DP20S830/20	120	6	3.55	330	2070	3000	80	50W	50,000	▲	★	Damp	Accent, 20° beam, Silver
		7	64494	LED7DP20S827/20	120	6	3.55	300	1900	2700	80	50W	50,000	▲	★	Damp	Accent, 20° beam, Silver
		7	63696	LED7DP20B827/15	120	6	3.55	300	3400	2700	80	50W	50,000	▲	★	Damp	Accent, 15° beam, Black
		7	67578	LED7DP20B827/35	120	6	3.55	300	840	2700	80	50W	25,000	▲	★	Damp	Accent, 35° beam, Black
		7	63023	LED7DP20S/NFL/TP	120	3	3.55	300	1900	2700	80	50W	50,000	▲	★	Damp	Accent, 20° beam, Silver
		7	90101	LED7DP202B830/15	120	6	3.5	520	5100	3000	83	70W	25,000	▲	★	Damp	Accent, 15° beam, Black
		7	90102	LED7DP202B830/20	120	6	3.5	520	3600	3000	83	70W	25,000	▲	★	Damp	Accent, 20° beam, Black
		7	94450	LED7DP202B827/15	120	6	3.5	500	5000	2700	83	70W	25,000	▲	★	Damp	Accent, 15° beam, Black
		7	99643	LED7DP20B827/20	120	6	3.5	500	3600	2700	83	70W	25,000	▲	★	Damp	Accent, 20° beam, Black
		7	70074	LED7DP20B827/35	120	6	3.5	500	1150	2700	83	65W	25,000	▲	★	Damp	Accent, 35° beam, Black
		7	94448	LED7DP202W830/15	120	6	3.5	520	5100	3000	83	70W	25,000	▲	★	Damp	Accent, 15° beam, White
		7	94449	LED7DP202W830/20	120	6	3.5	520	3600	3000	83	70W	25,000	▲	★	Damp	Accent, 20° beam, White
7	94452	LED7DP202W827/15	120	6	3.5	500	5000	2700	83	70W	25,000	▲	★	Damp	Accent, 15° beam, White		
7	99644	LED7DP20BW827/20	120	6	3.5	500	4000	2700	83	70W	25,000	▲	★	Damp	Accent, 20° beam, White		
7	89985	LED7DP202W/NFLTP	120	3	3.5	500	4000	2700	83	70W	25,000	▲	★	Damp	Accent, 20° beam, White		
Compact PAR30 – Low Glare – Visual Comfort Lens™ (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)																	
	MED	12	67922	LED12DP30R930/15	120	6	3.75	860	5650	3000	91	65W	25,000	▲	★	Dry	Accent, 15° beam, Silver, 65-w Repl.
		12	67923	LED12DP30R930/25	120	6	3.75	860	3100	3000	91	75W	25,000	▲	★	Dry	Accent, 25° beam, Silver, 75-w Repl.
		12	67924	LED12DP30R930/40	120	6	3.75	860	1350	3000	91	75W	25,000	▲	★	Dry	Accent, 40° beam, Silver, 75-w Repl.
		12	67925	LED12DP30R927/15	120	6	3.75	820	5350	2700	91	65W	25,000	▲	★	Dry	Accent, 15° beam, Silver, 65-w Repl.
		12	67926	LED12DP30R927/25	120	6	3.75	820	2950	2700	91	75W	25,000	▲	★	Dry	Accent, 25° beam, Silver, 75-w Repl.
		12	67927	LED12DP30R927/40	120	6	3.75	820	1300	2700	91	65W	25,000	▲	★	Dry	Accent, 40° beam, Silver, 65-w Repl.
Compact PAR30 – Long Neck – Low Glare – Visual Comfort Lens™ (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)																	
	MED	12	66050	LED12P3LS930/25	120	6	4.75	660	3000	3000	92	75W	25,000		★	Dry	Narrow Flood, 25° beam, Silver, 75-w Repl.
		12	66053	LED12P3LS927/40	120	6	4.75	630	900	2700	92	50W	25,000		★	Dry	Flood, 40° beam, Silver, 50-w Repl.
		12	68387	LED12DP3LR930/15	120	6	4.75	860	5650	3000	91	65W	25,000	▲	★	Dry	Accent, 15° beam, Silver, 65-w Repl.
		12	68388	LED12DP3LR930/25	120	6	4.75	860	3100	3000	91	75W	25,000	▲	★	Dry	Accent, 25° beam, Silver, 75-w Repl.
		12	68389	LED12DP3LR930/40	120	6	4.75	860	1350	3000	91	75W	25,000	▲	★	Dry	Accent, 40° beam, Silver, 75-w Repl.
		12	68390	LED12DP3LR927/15	120	6	4.75	820	5350	2700	91	65W	25,000	▲	★	Dry	Accent, 15° beam, Silver, 65-w Repl.
		12	68391	LED12DP3LR927/25	120	6	4.75	820	2950	2700	91	75W	25,000	▲	★	Dry	Accent, 25° beam, Silver, 75-w Repl.
		12	68392	LED12DP3LR927/40	120	6	4.75	820	1300	2700	91	65W	25,000	▲	★	Dry	Accent, 40° beam, Silver, 65-w Repl.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70).

** Minimum order quantity = 6

† Incandescent or halogen wattage equivalencies based on Energy Star guidelines using lumens or CBCP according to lamp type

†† Energy Star status: Certified as meeting Energy Star guidelines.

‡ UL 1993 Environmental Requirements for LED Lamps, see page 6-2.

Note: Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

For the most up-to-date product information, see www.gelighting.com. To convert inches to millimeters, multiply by 25.4. All footnote references found at the end of this section.