


LED Lamps and Systems


Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	†Wattage Equivalency	*Rated Life - Hours L70	‡Dimmable	††ENERGY STAR®	‡‡Location Rating	Additional Information
------------	-----------	-------	------------	-------------	-------	----------	----------	----------------	------	--------------------	-----	----------------------	-------------------------	-----------	----------------	-------------------	------------------------

Directional Lamps (PAR) (continued)

PAR38 - Low Glare - Visual Comfort Lens™ (90-watt halogen replacements - based on ENERGY STAR® requirements for center beam candlepower)

PAR38	MED																
	12	63228	LED12DP38W830/15	120	6	5.32	1000	13500	3000	80	90W	25,000	▲	★	Dry	Spot, 15° beam, White	
	12	63233	LED12DP38W830/25	120	6	5.32	1000	4800	3000	80	90W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	12	63235	LED12DP38W830/40	120	6	5.32	1000	1900	3000	80	90W	25,000	▲	★	Dry	Flood, 40° beam, White	
	12	63239	LED12DP38W827/15	120	6	5.32	960	12800	2700	80	90W	25,000	▲	★	Dry	Spot, 15° beam, White	
	12	63323	LED12DP38W827/25	120	6	5.32	960	4600	2700	80	90W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	12	63329	LED12DP38W827/40	120	6	5.32	960	1800	2700	80	90W	25,000	▲	★	Dry	Flood, 40° beam, White	
	12	63330	LED12DP38W930/15	120	6	5.32	860	11400	3000	91	90W	25,000	▲	★	Dry	Spot, 15° beam, White	
	12	63331	LED12DP38W930/25	120	6	5.32	860	4100	3000	91	90W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	12	63332	LED12DP38W930/40	120	6	5.32	860	1600	3000	91	90W	25,000	▲	★	Dry	Flood, 40° beam, White	
	12	63333	LED12DP38W927/15	120	6	5.32	820	11000	2700	91	90W	25,000	▲	★	Dry	Spot, 15° beam, White	
	12	63334	LED12DP38W927/25	120	6	5.32	820	3900	2700	91	90W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	12	63343	LED12DP38W927/40	120	6	5.32	820	1550	2700	91	90W	25,000	▲	★	Dry	Flood, 40° beam, White	
	14	67252	LED14P38S830/25	120	6	5.31	900	3600	3000	84	75W	25,000		★	Dry	Narrow Flood, 25° beam, Silver, 75-w Repl.	
	14	67253	LED14P38S830/40	120	6	5.31	900	1600	3000	84	90W	25,000		★	Dry	Flood, 40° beam, Silver, 90-w Repl.	
	14	67254	LED14P38S827/25	120	6	5.31	840	3500	2700	84	75W	25,000		★	Dry	Narrow Flood, 25° beam, Silver, 75-w Repl.	
	14	67255	LED14P38S827/40	120	6	5.31	840	1500	2700	84	75W	25,000		★	Dry	Flood, 40° beam, Silver, 75-w Repl.	
	14	69138	LED14P38S930/25	120	6	5.31	790	3050	3000	92	75W	25,000		★	Dry	Narrow Flood, 25° beam, Silver	
	14	69139	LED14P38S930/40	120	6	5.31	790	1400	3000	92	75W	25,000		★	Dry	Flood, 40° beam, Silver	
	14	69140	LED14P38S927/40	120	6	5.31	770	1350	2700	92	75W	25,000		★	Dry	Flood, 40° beam, Silver	
	17	61930	LED17P38S830/15	120	6	5.31	820	9000	3000	82	90W	50,000		★	Dry	Spot, 15° beam, Silver, 90-w Repl.	
	17	64035	LED17P38S830/17	120	6	5.31	820	7100	3000	82	90W	50,000		★	Dry	Spot, 17° beam, Silver, 90-w Repl.	
	17	61931	LED17P38S830/25	120	6	5.31	820	4500	3000	87	90W	50,000		★	Dry	Narrow Flood, 25° beam, Silver, 90-w Repl.	
	17	63105	LED17P38S927/15	120	6	5.31	670	7800	2700	90	75W	50,000			Dry	Spot, 15° beam, Silver, 75-w Repl.	
	17	65423	LED17P38S927/40	120	6	5.31	710	1300	2700	90	75W	50,000			Dry	Flood, 40° beam, Silver, 75-w Repl.	
	18	94909	LED18D38W830/15	120	6	5.31	1400	8700	3000	80	85W	25,000	▲	★	Dry	Spot, 15° beam, White	
	18	94549	LED18D38W830/25	120	6	5.31	1400	5100	3000	80	100W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	18	94910	LED18D38W830/40	120	6	5.31	1400	2800	3000	80	120W	25,000	▲	★	Dry	Flood, 40° beam, White	
	18	94903	LED18D38W930/15	120	6	5.31	1200	7500	3000	91	75W	25,000	▲	★	Dry	Spot, 15° beam, White	
	18	94904	LED18D38W930/25	120	6	5.31	1200	4400	3000	91	100W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White	
	18	94905	LED18D38W930/40	120	6	5.31	1200	2400	3000	91	120W	25,000	▲	★	Dry	Flood, 40° beam, White	
18	94901	LED18D38W927/15	120	6	5.31	1100	7100	2700	91	75W	25,000	▲	★	Dry	Spot, 15° beam, White		
18	94198	LED18D38W927/25	120	6	5.31	1100	4100	2700	91	95W	25,000	▲	★	Dry	Narrow Flood, 25° beam, White		
18	94902	LED18D38W927/40	120	6	5.31	1100	2300	2700	91	120W	25,000	▲	★	Dry	Flood, 40° beam, White		

Commercial PAR38 (Indoor/Outdoor) (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)

PAR38	MED																
	12	66111	LED12DP38S830/12	120	6	5.31	700	10000	3000	82	70W	25,000	▲	★	Damp	Spot, 12° beam, Silver, 70-w Repl.	
	12	66112	LED12DP38S830/25	120	6	5.31	700	3300	3000	82	70W	25,000	▲	★	Damp	Narrow Flood, 25° beam, Silver, 70-w Repl.	
	12	66113	LED12DP38S830/35	120	6	5.31	700	1500	3000	82	65W	25,000	▲	★	Damp	Flood, 35° beam, Silver, 65-w Repl.	
	12	66529	LED12DP38/FL/TP	120	3	5.31	700	1500	3000	82	65W	25,000	▲	★	Damp	Flood, 35° beam, Silver, 65-w Repl.	
	12	66114	LED12DP38S827/12	120	6	5.31	660	10000	2700	82	70W	25,000	▲	★	Damp	Spot, 12° beam, Silver, 70-w Repl.	
	12	66115	LED12DP38S827/25	120	6	5.31	660	3300	2700	82	70W	25,000	▲	★	Damp	Narrow Flood, 25° beam, Silver, 70-w Repl.	

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70).

** Minimum order quantity = 6

† Incandescent or halogen wattage equivalencies based on Energy Star guidelines using lumens or CBCP according to lamp type

†† Energy Star status: Certified as meeting Energy Star guidelines.

‡ UL 1993 Environmental Requirements for LED Lamps, see page 6-2.

Note: Product descriptions ending in "T/P" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.