


27218 - 80PAR/HIR/FL25

GE HIR™ PAR38

- Up to 20% longer life -3000 hours
- Up to 28% more efficient than standard halogen Up to 22% energy savings

a product of

ecomagination-











CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GENERAL CHARACTERISTICS

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)

Filament CC-8 Rated Life (NOM) 3000.0 h

Primary Application Indoor and outdoor

Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1500.0 Center Beam Candlepower 5000.0

(CBCP) (NOM)

Color Temperature (NOM) 2900.0 K Beam Spread (NOM) 25.0 ° Nominal Initial Lumens per Watt 18.75

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 80.0 Voltage (NOM) 120.0

DIMENSIONS

Maximum Overall Length 5.313 in(135.0 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code 27218

Description 80PAR/HIR/FL25

Standard Package Case

Standard Package GTIN 10043168272183

Standard Package Quantity

Sales Unit

No Of Items Per Sales Unit

No Of Items Per Standard

12

Package

UPC 043168272186