

Item Number	ENERGY STAR®	Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	*CBCP	Beam Angle	CCT	CRI	STK/MTO	Case Quantity
-------------	--------------	------------------	---------	------------	--------	-----------------	-------	------------	-----	-----	---------	---------------

Non Dimmable  
Designer Elite  
LED PAR  
Lamps

**12W ELITE DESIGNER NON DIMMABLE PAR30 SHORT NECK (REPLACES 75W)**

LED12P30S24KFL		12W Smooth PAR30 SN - 2400K 40 Degree	120	12	800	66.7	1315	40	2400K	82	MTO	12
LED12P30S24KNFL		12W Smooth PAR30 SN - 2400K 25 Degree	120	12	800	66.7	2910	25	2400K	82	MTO	12
LED12P30S24KSP		12W Smooth PAR30 SN - 2400K 15 Degree	120	12	800	66.7	6155	15	2400K	82	MTO	12
LED12P30S27KFL		12W Smooth PAR30 SN - 2700K 40 Degree	120	12	800	66.7	1315	40	2700K	82	STK	12
LED12P30S27KNFL	★	12W Smooth PAR30 SN - 2700K 25 Degree	120	12	800	66.7	2910	25	2700K	82	STK	12
LED12P30S27KSP		12W Smooth PAR30 SN - 2700K 15 Degree	120	12	800	66.7	6155	15	2700K	82	MTO	12
LED12P30S30KFL		12W Smooth PAR30 SN - 3000K 40 Degree	120	12	825	68.8	1315	40	3000K	82	STK	12
LED12P30S30KNFL		12W Smooth PAR30 SN - 3000K 25 Degree	120	12	825	68.8	2910	25	3000K	82	STK	12
LED12P30S30KSP		12W Smooth PAR30 SN - 3000K 15 Degree	120	12	825	68.8	6155	15	3000K	82	MTO	12
LED12P30S35KFL		12W Smooth PAR30 SN - 3500K 40 Degree	120	12	850	70.8	1315	40	3500K	82	MTO	12
LED12P30S35KNFL		12W Smooth PAR30 SN - 3500K 25 Degree	120	12	850	70.8	2910	25	3500K	82	MTO	12
LED12P30S35KSP		12W Smooth PAR30 SN - 3500K 15 Degree	120	12	850	70.8	6155	15	3500K	82	MTO	12
LED12P30S41KFL		12W Smooth PAR30 SN - 4100K 40 Degree	120	12	875	72.9	1315	40	4100K	82	MTO	12
LED12P30S41KNFL		12W Smooth PAR30 SN - 4100K 25 Degree	120	12	875	72.9	2910	25	4100K	82	MTO	12
LED12P30S41KSP		12W Smooth PAR30 SN - 4100K 15 Degree	120	12	875	72.9	6155	15	4100K	82	MTO	12
LED12P30S50KFL		12W Smooth PAR30 SN - 5000K 40 Degree	120	12	875	72.9	1315	40	5000K	82	MTO	12
LED12P30S50KNFL		12W Smooth PAR30 SN - 5000K 25 Degree	120	12	875	72.9	2910	25	5000K	82	MTO	12
LED12P30S50KSP		12W Smooth PAR30 SN - 5000K 15 Degree	120	12	875	72.9	6155	15	5000K	82	MTO	12



**10W ELITE DESIGNER NON DIMMABLE PAR30 SHORT NECK (REPLACES 60W)**

LED10P30S24KFL		10W Smooth PAR30 SN - 2400K 40 Degree	120	10	600	60.0	957	40	2400K	82	MTO	12
LED10P30S24KNFL		10W Smooth PAR30 SN - 2400K 25 Degree	120	10	600	60.0	2118	25	2400K	82	MTO	12
LED10P30S24KSP		10W Smooth PAR30 SN - 2400K 15 Degree	120	10	600	60.0	4480	15	2400K	82	MTO	12
LED10P30S27KFL	★	10W Smooth PAR30 SN - 2700K 40 Degree	120	10	600	60.0	957	40	2700K	82	STK	12
LED10P30S27KNFL	★	10W Smooth PAR30 SN - 2700K 25 Degree	120	10	600	60.0	2118	25	2700K	82	STK	12
LED10P30S27KSP		10W Smooth PAR30 SN - 2700K 15 Degree	120	10	600	60.0	4480	15	2700K	82	MTO	12
LED10P30S30KFL		10W Smooth PAR30 SN - 3000K 40 Degree	120	10	650	65.0	957	40	3000K	82	STK	12
LED10P30S30KNFL		10W Smooth PAR30 SN - 3000K 25 Degree	120	10	650	65.0	2118	25	3000K	82	STK	12
LED10P30S30KSP		10W Smooth PAR30 SN - 3000K 15 Degree	120	10	650	65.0	4480	15	3000K	82	MTO	12
LED10P30S35KFL		10W Smooth PAR30 SN - 3500K 40 Degree	120	10	675	67.5	957	40	3500K	82	MTO	12
LED10P30S35KNFL		10W Smooth PAR30 SN - 3500K 25 Degree	120	10	675	67.5	2118	25	3500K	82	MTO	12
LED10P30S35KSP		10W Smooth PAR30 SN - 3500K 15 Degree	120	10	675	67.5	4480	15	3500K	82	MTO	12
LED10P30S41KFL		10W Smooth PAR30 SN - 4100K 40 Degree	120	10	700	70.0	957	40	4100K	82	MTO	12
LED10P30S41KNFL		10W Smooth PAR30 SN - 4100K 25 Degree	120	10	700	70.0	2118	25	4100K	82	MTO	12
LED10P30S41KSP		10W Smooth PAR30 SN - 4100K 15 Degree	120	10	700	70.0	4480	15	4100K	82	MTO	12
LED10P30S50KFL		10W Smooth PAR30 SN - 5000K 40 Degree	120	10	700	70.0	957	40	5000K	82	MTO	12
LED10P30S50KNFL		10W Smooth PAR30 SN - 5000K 25 Degree	120	10	700	70.0	2118	25	5000K	82	MTO	12
LED10P30S50KSP		10W Smooth PAR30 SN - 5000K 15 Degree	120	10	700	70.0	4480	15	5000K	82	MTO	12

★ ENERGY STAR® Rated (at time of print)



\*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.

LED Lamps

TCP CATALOG  
800.324.1496 | tcp.com