

**Non Dimmable
Designer Elite
LED PAR
Lamps**



10W ELITE DESIGNER NON DIMMABLE PAR20 (REPLACES 60W)

Item Number	ENERGY STAR®	Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	* CBCP	Beam Angle	CCT	CRI	STK/MTD	Case Quantity
LED10P2024KFL		10W Smooth PAR20 - 2400K 40 Degree	120	10	600	60.0	1558	40	2400K	82	MTD	12
LED10P2024KNFL		10W Smooth PAR20 - 2400K 25 Degree	120	10	600	60.0	3067	25	2400K	82	MTD	12
LED10P2027KFL		10W Smooth PAR20 - 2700K 40 Degree	120	10	600	60.0	1558	40	2700K	82	STK	12
LED10P2027KNFL	★	10W Smooth PAR20 - 2700K 25 Degree	120	10	600	60.0	3067	25	2700K	82	STK	12
LED10P2030KFL	★	10W Smooth PAR20 - 3000K 40 Degree	120	10	650	65.0	1558	40	3000K	82	STK	12
LED10P2030KNFL		10W Smooth PAR20 - 3000K 25 Degree	120	10	650	65.0	3067	25	3000K	82	STK	12
LED10P2035KFL		10W Smooth PAR20 - 3500K 40 Degree	120	10	675	67.5	1558	40	3500K	82	MTD	12
LED10P2035KNFL		10W Smooth PAR20 - 3500K 25 Degree	120	10	675	67.5	3067	25	3500K	82	MTD	12
LED10P2041KFL		10W Smooth PAR20 - 4100K 40 Degree	120	10	700	70.0	1558	40	4100K	82	MTD	12
LED10P2041KNFL		10W Smooth PAR20 - 4100K 25 Degree	120	10	700	70.0	3067	25	4100K	82	MTD	12
LED10P2050KFL		10W Smooth PAR20 - 5000K 40 Degree	120	10	700	70.0	1558	40	5000K	82	MTD	12
LED10P2050KNFL		10W Smooth PAR20 - 5000K 25 Degree	120	10	700	70.0	3067	25	5000K	82	MTD	12

8W ELITE DESIGNER NON DIMMABLE PAR20 (REPLACES 50W)

LED8P2024KFL		8W Smooth PAR20 - 2400K 40 Degree	120	8	500	62.5	593	40	2400K	82	MTD	12
LED8P2024KNFL		8W Smooth PAR20 - 2400K 25 Degree	120	8	500	62.5	1179	25	2400K	82	MTD	12
LED8P2027KFL		8W Smooth PAR20 - 2700K 40 Degree	120	8	500	62.5	593	40	2700K	82	STK	12
LED8P2027KNFL	★	8W Smooth PAR20 - 2700K 25 Degree	120	8	500	62.5	1179	25	2700K	82	STK	12
LED8P2030KFL	★	8W Smooth PAR20 - 3000K 40 Degree	120	8	515	64.4	593	40	3000K	82	STK	12
LED8P2030KNFL		8W Smooth PAR20 - 3000K 25 Degree	120	8	515	64.4	1179	25	3000K	82	STK	12
LED8P2035KFL		8W Smooth PAR20 - 3500K 40 Degree	120	8	525	65.6	593	40	3500K	82	MTD	12
LED8P2035KNFL		8W Smooth PAR20 - 3500K 25 Degree	120	8	525	65.6	1179	25	3500K	82	MTD	12
LED8P2041KFL		8W Smooth PAR20 - 4100K 40 Degree	120	8	530	66.3	593	40	4100K	82	MTD	12
LED8P2041KNFL		8W Smooth PAR20 - 4100K 25 Degree	120	8	530	66.3	1179	25	4100K	82	MTD	12
LED8P2050KFL		8W Smooth PAR20 - 5000K 40 Degree	120	8	530	66.3	593	40	5000K	82	MTD	12
LED8P2050KNFL		8W Smooth PAR20 - 5000K 25 Degree	120	8	530	66.3	1179	25	5000K	82	MTD	12

★ ENERGY STAR® Rated (at time of print)



*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.