

65847 - LED20DP38/FL/TP

GE LED 20 watt PAR38 floodlight 1-pack

• The future of lighting is here. GE energy smart® LED directional bulbs deliver the technology and flexibility to make the most of your living spaces. GE energy smart® LED indoor floodlights provide a broad beam of light in track and recessed fixtures. These bulbs offer an energy-efficient, long-lasting indoor lighting solution, perfect for hard-to-reach sockets that are frequently left on.

Lasts 22.8 years based on 3 hours per day usage

- Estimated yearly energy costs \$2.41 based on 3 hours per day \$0.11 per kWh
- \$151 in energy savings over the life of the bulb based on 3 hours per day usage

PAR38 indoor/outdoor floodlight with medium base for use in outdoor security lighting and indoor directional fixtures







GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Additional Info

Bulb Shape Color Dimming Capability

Equivalent Wattage (NOM) Lamp Type Life in Years (NOM) Rated Life (NOM) Replacement Lamps -Directional PAR38 Medium Screw (E26) GE Life Rating is based on 70% Lumen Maintenance PAR38 Silver Operates on dimming circuits. See GELighting.com/dimming for further information 90.0 W LED-PAR 22.8 25000.0 h

PHOTOMETRIC CHARACTERISTICS

Beam Spread (NOM)40.0 °Center Beam Candlepower1700.0(CBCP) (NOM)0Color Rendering Index80.0(CRI) (NOM)2700.0 KColor Temperature (NOM)2700.0 KInitial Lumens (NOM)1000.0Lumens per Watt (Efficacy)50.0 lm(NOM)Nominal Initial Lumens per50.0Watt (NOM)50.0

ELECTRICAL CHARACTERISTICS

Estimated Energy Cost per 2.41 Year (NOM) Voltage (NOM) 120.0 Wattage (NOM) 20.0

DIMENSIONS

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm) Maximum Overall Length 5.310 in(134.9 mm) (MOL) (NOM)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168658478