

GU24 OMNIDIRECTIONAL A19 LED LAMP



MaxLite's LED GU24 Omni A19 lamps are the most versatile GU24-based light sources in the market. They replicate a true A19 incandescent replacement lamp with a 300-degree beam angle that produces even light from the socket base and above in all directions. The seven-, 10- and 15-watt GU24 lamps emit light equivalent to 40-, 60- and 75-watt incandescent bulbs respectively. MaxLED®'s LED Omni A19 Lamps can yield up to 85 percent savings in energy. Lumen maintenance is maximized by using a multi layer tapered heat sink.

FEATURES:

- 2700K, 3000K & 4100K CCTs
- Proprietary housing for thermal heat protection
- CRI: 80
- Five year limited warranty
- Dimmable down to 10 percent
- Saves up to 85 percent on energy and operating costs
- Power factor: > .9
- Not for use in totally enclosed luminaires
- Suitable for use in dry or damp locations

APPLICATIONS:

- Chandeliers
- Pendants
- Table and floor lamps
- Sconces
- Bathroom fixtures

CONSTRUCTION:

LEDs: All LEDs are matched to ensure consistent color uniformity and CRI. The stated L70 life is based on functional light quality.

Housing: The body of each lamp is constructed of aluminum and plastic materials. The tiered heat sink promotes heat dissipation and features a tapered look. This keeps the LED junction temperature well below the manufacturer's specification. The temperature of the LED chips stay within proper thermal limits and the lumens are maintained for longer life.

Base: The Omni A19 lamp has a GU24 base.

Lamp Ordering Information:

Watts	Order Number	Model Number	Incand. Equiv. Wattage	Delivered Lumens	Beam	Lamp Life (Hrs.)	Dimensions	CCT
7	72343	SKBO07GUDLED27	40	435	300°	25,000	2.45" X 4.43"	2700
7	72078	SKBO07GUDLED30	40	450	300°	25,000	2.45" X 4.43"	3000
7	72550	SKBO07GUDLED41	40	460	300°	25,000	2.45" X 4.43"	4100
10	72342	SKBO10GUDLED27	60	770	300°	25,000	2.45" X 4.43"	2700
10	72063	SKBO10GUDLED30	60	800	300°	25,000	2.45" X 4.43"	3000
10	72215	SKBO10GUDLED41	60	825	300°	25,000	2.45" X 4.43"	4100
15	72229	SKBO15GUDLED27	75	1050	300°	25,000	2.75" X 5.1"	2700
15	72134	SKBO15GUDLED30	75	1100	300°	25,000	2.75" X 5.1"	3000
15	72230	SKBO15GUDLED41	75	1130	300°	25,000	2.75" X 5.1"	4100



Lighting layouts and spacing criteria available upon request

*ENERGY STAR certified subcomponent

†Qualified on ENERGY STAR lamps program



Revised: 06-17-14

MAX13003

GU24 OMNIDIRECTIONAL A19 LED LAMP



SKBO07GUDLED27
SKBO07GUDLED30
SKBO10GUDLED27
SKBO10GUDLED30
SKBO10GUDLED41



SKBO15GUDLED27
SKBO15GUDLED30

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL
Lutron	TG-600PR
	S-600PR
	CT-103P
	CTCL-153
	DVCL-153L
	TGCL-153PH
Leviton	cat.NO.6683-P

