

## 97635 - F42TBX/835/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









# **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

### **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-Bulb T4 Base GX24-q4 Equivalent Wattage (NOM) 190.0 W 17000.0 h Rated Life (NOM) Starting Temperature (MIN) -18.0 °C Cathode Resistance (NOM) 2.7 Ohm Mercury Content (NOM) 3.0 mg 65.6 pg Picograms of Mercury (NOM)

Rated Life (rapid start) @ Time 17000.0 @ 3.0/20000.0 @

12.0 h

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant

Primary Application Facilities; Retail

Display;Hospitality;Office;Restaurant;W

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 3200.0
Mean Lumens (NOM) 2690.0
Nominal Initial Lumens per Watt (NOM)
Color Temperature (NOM) 3500.0 K

Color Temperature (NOM) 3500.0 K
Color Rendering Index (CRI) 82.0

(NOM)

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 42.0 Voltage (NOM) 135.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 265.0 V preheating) (MAX) Open Circuit Voltage (MIN) 515.0 V Lamp Current (NOM) 0.32 A Preheat Voltage (MIN) 4.25 V Current Crest Factor (MAX) 1.7 Supply Current Frequency 20.0 Hz

(NOM)

## **DIMENSIONS**

Maximum Overall Length (MOL) (NOM)

Nominal Length (NOM)

Base Face to Top of Lamp

6.400 in(162.6 mm)
6.400 in(162.6 mm)
5.770 in(146.6 mm)

(NOM)

# **PRODUCT INFORMATION**

Product Code 97635

 Description
 F42TBX/835/A/ECO

 ANSI Code
 60901-IEC-7442-2

Standard Package Case

Standard Package GTIN 10043168976357

Standard Package Quantity

Sales Unit

No Of Items Per Sales Unit

No Of Items Per Standard

10

Package

UPC 043168976350

#### NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life