


## 42072 - 35PAR36/H/VWFL

## GE PAR36 - Very Wide Flood

• Standard Halogen - Crisp, white light









#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

## Warning

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- A damaged lamp emits UV radiation which may cause eye/skin injury
- Turn power off if glass bulb is broken. Remove and dispose of lamp.
- $\bullet$  Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.

## **GENERAL CHARACTERISTICS**

Lamp Type Sealed Beam - PAR

Bulb PAR36

Base Screw Terminals

Filament C-6 Rated Life (NOM) 4000.0 h

Primary Application Very Wide Flood

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 400.0
Beam Spread - Horizontal 140.0 - 10.0 °
Beam Spread - Vertical 140.0 - 10.0 °
Color Temperature (NOM) 3050.0 K
Nominal Initial Lumens per Watt 11.42857

(NOM)

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 35.0 Voltage (NOM) 12.0

Burn Position Universal burning position

#### **DIMENSIONS**

Maximum Overall Length 2.750 in(69.8 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.500 in(114.3 mm)

# **PRODUCT INFORMATION**

Product Code 42072

Description 35PAR36/H/VWFL

Standard Package Case

Standard Package GTIN 10043168420720

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

12

Package

UPC 043168420723