

# 13895 - FCM/HIR-Q650T3/4

GE Quartzline® HIR™ Showbiz® T3 - Stage & Studio





#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp emits UV radiation which may cause eye/skin irritation.
- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- · Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.
- Dispose of lamp in a closed container.
- Wear safety glasses and gloves when handling lamp.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Use eve protection when handling lamp.
- Do not touch glass with bare hands.
- Use in enclosed fixture rated for this product.
- Do not use lamp if outer glass is scratched or broken.
- Operate lamp only in specified position.
- Do not exceed 110% of rated voltage or 105% of rated current.

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base

Filament **Bulb Finish** Rated Life (NOM) **Primary Application**  Halogen - Double-Ended T3 **Recessed Single Contact** (R7s) C-8 Clear 400.0 h Stage & Studio

# **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) Color Temperature (NOM) Nominal Initial Lumens per Watt 38.76923 (NOM)

25200.0 3275.0 K

## **ELECTRICAL CHARACTERISTICS**

#### Wattage (NOM) 650.0

#### Voltage (NOM) Burn Position

120.0 Operate only horizontally within 4°

# DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM)

4.680 in(118.9 mm) 0.375 in(9.5 mm)

# **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

13895 FCM/HIR-Q650T3/4 FCM Case 10043168138953 6 Unit 1 6

043168138956