

Incandescent Lamps

Watts	Bulb Base	Product Number	Symbols, Footnotes	Ordering Code	Pkg. Qty. ‡	Description	Class Filament	LCL (In.)	MOL (In.)	Rated Avg. Life (Hrs.) ⁽⁹³⁾	Approx. MBCP ¹	Life Years (446)	Energy Cost (445)	Color Temp. (K)
Incandescent Lamps by Wattage (Continued)														
FTC REQUIREMENTS*														
50	R20 Med.	41531-5	(19,87)▲†	50R20/Agro 12/1	120 12	Agro-Lite Plant Light	C, CC-6	3 5/16		2000		1.8	\$6.02	
50	A21 3 Ct. Med.	13564-0	(8)▲	50/150A/NTL 12/1	120 12	Natural Light Reflector	C,2CC-6	5 5/16		1200		395	1.1	\$6.02 2590
100												1115	\$12.05	3100
150												1510	\$18.07	3050
		16948-2	(8)▲	50/150A/WL 12/1	120 12	Soft White Long Life 3-Way	C, 2CC-8	5 5/16	1750			460	1.6	\$6.02 2720
												1165	\$12.05	2810
		32359-2	(8)□▲	50/150A/DL 12/1	120 12	Director 3-Way	C, 2CC-8	5 5/16	1200			1660	\$18.07	2780
												520	1.1	\$6.02 2670
												1320	\$12.05	2780
												1840	\$18.07	2740
52	A19 Med.	22237-2	▲✓	60A-52A/EW	120 48	Frost Econ-o-watt	C, CC-6	4 7/16	1000			700	0.9	\$6.26 2760
		14999-6	▲	60A-52A/99/EW	120-130	Frost Econ-o-watt Ext. Service Ratings @ 130V = 60W	C, CC-6	4 7/16	2000	1000		650	0.9	\$6.26 2700
												855	0.9	\$7.23 2780
60	A15 Med.	16945-8	▲	BC60A15/FANW/LL 6/2	120 12	White Long Life Fan	C, C-9	3 1/2	2000			570	1.8	\$7.23
		16946-6	▲	BC60A15/FAN/CL/LL 6/2	120 12	Clear Long Life Fan	C, C-9	3 1/2	2000			630	1.8	\$7.23
	A19 Med. ++	16794-0	▲	60A/CL/LL 12/2	120 24	Clear Long Life	C, CC-6	4 7/16	1500			865	1.4	\$7.23 2760
		16874-0	▲	60A/WL 12/4	120 48	Soft White Long Life	C, CC-6	4 7/16	1500			830	1.4	\$7.23 2750
	Med.	13559-0	▲	60A/NTL 12/4	120 48	Natural Light Standard	C, CC-6	4 7/16	1000			640	0.9	\$7.23 2790
	Med. ++	27082-7	▲✓	60A 12/4	120 48	Frost	C, CC-6	4 7/16	1000			890	0.9	\$7.23 2760
		37469-4	▲✓	60A	120 48	Frost	C, CC-6	4 7/16	1000			840	0.9	\$7.23 2790
		37471-0	▲✓	60A	130 48	Frost	C, CC-6	4 7/16	1000	2000		855	0.9	\$7.23 2780
						Ratings @ 120V =51W						650	1.8	\$6.14 2700
	Med.	14979-9	(66)▲	60A/TF	120 120	Frost Silicone Coated	C, CC-6	4 7/16	1000			0.9	\$7.23	
	Med. ++	22246-3	▲✓	60A/99	130 48	Frost Extended Service Ratings @ 120V =51W	C, CC-6	4 7/16	2500	5000		720	2.3	\$7.23 2670
												540	4.6	\$6.14 2590
		37522-0	▲	60A/CL	130 48	Clear	C, CC-6	3 5/16 4 7/16	500	1000		965	0.5	\$7.23 2820
						Ratings @ 120V =51W						730	0.9	\$6.14 2740
	Med.	41534-9	▲†	60A/AGRO 12/1	120 12	Agro-Lite Plant Light	C, C-9	4 7/16	1000			0.9	\$7.23	
		41543-0	▲†	BC60A/CL/GDO 6/2	120 6	Garage Door Opener	C,C-9	4 7/16	3500			630	3.2	\$7.23
	Med. ++	37483-5	▲✓	60A/W 12/4	120 48	Soft White	C, CC-6	4 7/16	1000			860	0.9	\$7.23 2770
		37484-3	▲	60A/W/TP 24/4	120 96	Soft White Tray-Pak	C, CC-6	4 7/16	1000			860	0.9	\$7.23 2770
		34822-7	□▲	60A/STP/PK 12/2	120 24	Pink Softone Pastel	C, CC-6	4 7/16	1000			795	0.9	\$7.23 2610
		41581-0	□▲†✓	60A/YL 12/2	120 24	Bug-A-Way Yellow Longer Life	C, CC-6	4 7/16	1350				1.2	\$7.23
		22248-9	□	60A 19/35	130 48	Frost Industrial Service Ratings @ 120V = 51W	C, C-9	4 7/16	1750	3500		540	1.6	\$7.23 2590
												395	3.2	\$6.14 2500
	T10 Med.	13811-5	▲	60T10/64IF 24/1	120 24	Frost	B, C-8	5 5/16	1000			515	0.9	\$7.23 2630
		13810-7	▲	60T10/64 24/1	120 24	Clear	B, C-8	5 5/16	1000			520	0.9	\$7.23 2620

For the most current product information, go to the e-catalog on www.philips.com
Incandescent symbols and footnotes located on page 132

