Shown actual size: Centurion dimmer and 1-gang wallplate in White (WH).

Product family features

- Rotary style dimmer with captive knob
- Heavy duty components for surge protection and long product life
- Visible heat sink
- Gangable without removing side sections and reducing wattage
- Voltage compensation maintains stable light levels, despite line voltage variations
- Mechanical air-gap to disconnect load power
- 100% factory tested
- Original thick profile does not fit flush against the wall; for thinner profile see Nova T☆® on pg. 25
- Coordinating 1-gang wallplate included
- Custom engraving and custom coloring available for wallplates, see pg. 164

Control types

Single-pole (one location)

3-way or 4-way (two or more locations)

Direct load type compatibility

Incandescent/halogen lighting

Lighting load interfaces are not compatible with this family.

Architectural matte finishes*

WH White

BE Beige

Download specification submittal
Download high resolution product image

*Coordinating wallplate included with Architectural matte controls.

Rotary dimmers

- Rotate or push on/off (depending on model), rotate to adjust light level
- Higher capacity loads require large controls

Incandescent/halogen dimmers
(small controls)

Rotary, rotate on/off

Single-pole 120V 600W	C-600-**XX**[1]
Single-pole 120V 1000W	C-1000-**XX**[1]

Rotary, push on/off

Single-pole (small) 120V 600W	C-600P-**XX**[1]
Single-pole (small) 120V 1000W	C-10P-**XX**[1]
3-way (small) 120V 600W	C-603P-**XX**[1]
3-way (small) 120V 1000W	C-103P-**XX**[1]

Multi-gang wallplates are not available.

When ganging controls, mount single-gang wallplates side-by-side. Not gangable with other dimmer families.

Wider-than-standard electrical backboxes may be required.

For 3-way and 4-way switching, use a 3-way dimmer with mechanical switches.

Rotary dimmers

- Higher capacity dimmers require larger heat sink behind wallplate
- Rotate or push on/off (depending on model), rotate to adjust light level
- Measures 4.56in x 4.56in
- Requires large wallplate
- Most can fit in a 1-gang electrical backbox

Incandescent/halogen dimmers
(small controls)

Rotary, rotate on/off

Single-pole 120V 1500W	C-1500-**XX**[1]
Single-pole 120V 2000W	C-2000-**XX**[1]

Multi-gang wallplates are not available.

When ganging controls, mount single-gang wallplates side-by-side. Not gangable with other dimmer families.

Wider-than-standard electrical backboxes may be required.

For 3-way and 4-way switching, use a 3-way dimmer with mechanical switches.

XX[1]: Architectural matte White (WH) and Beige (BE), see pg. 45 (1-gang wallplate included)

All models must be derated if ganged, unless otherwise noted, see pg. 179.