

spotlight



The energy-efficient radiance of the GE energy smart® LED PAR30 short and long neck lamps is not just something you see, it's something you feel.

GE energy smart® LED PAR30 short and long neck lamps

For efficient, long-lasting options for traditional downlight applications, GE energy smart® dimmable 10-watt LED PAR30 lamps are the perfect solution.

LOW-COST OPERATION:

- Using only 12 watts of energy, save over \$104 in energy costs over the rated life of a lamp versus a standard 50-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80 to 92

COLOR TEMPERATURE

- Halogen-like color
- Available in 2700K, 3000K and 4000K

LONG LIFE

- Up to 30,000 hours rated life (L70)
- Up to 50,000 hours rated life (L70) for dimmable version

DIMMABLE

- Dims from 100% to 10%

BEAM PATTERNS

- Available in 20°, 24°, 25°, 35° and 40° beam patterns

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM



imagination at work

PERFORMANCE DATA

GE energy smart® LED PAR30 short and long neck lamps

| BULB SHAPE | BASE TYPE | WATTS | ORDER CODE | DESCRIPTION | VOLTS | CASE QTY** | MOL (IN) | LUMENS INITIAL | CBCP | INITIAL COLOR TEMP | CRI | +RATED LIFE (YRS) 3HRS/DAY | *RATED LIFE (HRS) | ESTIMATED ENERGY COST/YR | ENERGY STAR® STATUS | ADDITIONAL INFORMATION |
|--|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|----------------------------|-------------------|--------------------------|---------------------|--------------------------|
| Retail PAR30 - Dimming (Visual Comfort Lens™) | | | | | | | | | | | | | | | | |
| PAR30 | MED | 12 | 67922 | LED12DP30R930/15 | 120 | 6 | 3.75 | 860 | 5900 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 15° Beam, Silver |
| | | | 67923 | LED12DP30R930/25 | 120 | 6 | 3.75 | 860 | 3400 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Silver |
| | | | 67924 | LED12DP30R930/40 | 120 | 6 | 3.75 | 860 | 1500 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 40° Beam, Silver |
| | | | 67925 | LED12DP30R927/15 | 120 | 6 | 3.75 | 820 | 5700 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 15° Beam, Silver |
| | | | 67926 | LED12DP30R927/25 | 120 | 6 | 3.75 | 820 | 3300 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Silver |
| | | | 67927 | LED12DP30R927/40 | 120 | 6 | 3.75 | 820 | 1400 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 40° Beam, Silver |
| Compact PAR30 - Dimming (Concave Cover) | | | | | | | | | | | | | | | | |
| PAR30 | MED | 12 | 65135 | LED12DP30S830/20 | 120 | 6 | 3.75 | 750 | 5100 | 3000 | 84 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 20° Beam, Silver |
| | | | 65136 | LED12DP30S830/35 | 120 | 6 | 3.75 | 750 | 2050 | 3000 | 84 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver |
| | | | 65137 | LED12DP30S827/20 | 120 | 6 | 3.75 | 740 | 5000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 20° Beam, Silver |
| | | | 65138 | LED12DP30S827/35 | 120 | 6 | 3.75 | 740 | 2000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver |
| | | | 65133 | LED12DP30S/FL/TP | 120 | 3 | 3.75 | 740 | 2000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver |
| | | | 65985 | LED12DP30S827/25 | 120 | 6 | 3.75 | 740 | 3200 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Silver |
| | | | 65986 | LED12DP30W827/25 | 120 | 6 | 3.75 | 740 | 3200 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, White |
| | | | 65987 | LED12DP30B827/25 | 120 | 6 | 3.75 | 740 | 3200 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Black |
| | | | 67256 | LED12DP30S840/20 | 120 | 6 | 3.75 | 840 | 5800 | 4000 | 85 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 20° Beam, Silver |
| | | | 67257 | LED12DP30S840/35 | 120 | 6 | 3.75 | 840 | 2600 | 4000 | 85 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver |
| Compact PAR30 - Dimming (Convex Cover) | | | | | | | | | | | | | | | | |
| PAR30 | MED | 10 | 61922 | LED10DP30S830/20 | 120 | 6 | 3.75 | 500 | 3720 | 3000 | 80 | 45.7 | 50,000 | \$1.20 | ★ | Accent, 20° Beam, Silver |
| | | | 61923 | LED10DP30S827/20 | 120 | 6 | 3.75 | 450 | 3450 | 2700 | 80 | 45.7 | 50,000 | \$1.20 | ★ | Accent, 20° Beam, Silver |
| | | | 68013 | LED10DP30S827/35 | 120 | 6 | 3.75 | 450 | 1240 | 2700 | 80 | 22.8 | 25,000 | \$1.20 | ★ | Accent, 35° Beam, Silver |
| | | | 64326 | LED10DP30W827/20 | 120 | 6 | 3.75 | 450 | 3450 | 2700 | 80 | 45.7 | 50,000 | \$1.20 | ★ | Accent, 20° Beam, White |
| | | | 63026 | LED10DP3/FL/TP | 120 | 3 | 3.75 | 450 | 1240 | 2700 | 80 | 22.8 | 25,000 | \$1.20 | ★ | Accent, 20° Beam, Silver |

For additional product and application information, please consult GE's website: gelighting.com/ThinkLED

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® qualified

^ Estimated energy cost per year based on \$0.11 per kWh energy rate and 3 operating hours per day

Note: Product descriptions ending in "TP" indicate a card blister or clamshell package nested in a tray for shelf display.

Cards also designed for hook display.

ecomaginationSM



imagination at work

PERFORMANCE DATA

GE energy smart® LED PAR30 short and long neck lamps

| BULB SHAPE | BASE TYPE | WATTS | ORDER CODE | DESCRIPTION | VOLTS | CASE QTY* | MOL (IN) | LUMENS INITIAL | CBCP | INITIAL COLOR TEMP | CRI | +RATED LIFE (YRS) 3HRS/DAY | *RATED LIFE (HRS) | ESTIMATED ENERGY COST/YR | ENERGY STAR® STATUS | ADDITIONAL INFORMATION |
|---|-----------|-------|-------------------|-------------|-------|-----------|----------|----------------|------|--------------------|------|----------------------------|-------------------|--------------------------|--------------------------------|------------------------|
| Retail PAR30 Long Neck - Dimming (Visual Comfort Lens™) | | | | | | | | | | | | | | | | |
| PAR30L MED | 12 | 68387 | LED12DP3LR930/15 | 120 | 6 | 4.75 | 860 | 5900 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 15° Beam, Silver | |
| | | 68388 | LED12DP3LR930/25 | 120 | 6 | 4.75 | 860 | 3400 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Silver | |
| | | 68389 | LED12DP3LR930/40 | 120 | 6 | 4.75 | 860 | 1500 | 3000 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 40° Beam, Silver | |
| | | 68390 | LED12DP3LR927/15 | 120 | 6 | 4.75 | 820 | 5700 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 15° Beam, Silver | |
| | | 68391 | LED12DP3LR927/25 | 120 | 6 | 4.75 | 820 | 3300 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 25° Beam, Silver | |
| | | 68392 | LED12DP3LR927/40 | 120 | 6 | 4.75 | 820 | 1400 | 2700 | 91 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 40° beam, Silver | |
| Compact PAR30 Long Neck - Dimming (Concave Cover) | | | | | | | | | | | | | | | | |
| PAR30 MED | 12 | 65139 | LED12DP3LS830/20 | 120 | 6 | 4.75 | 750 | 5100 | 3000 | 84 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 20° Beam, Silver | |
| | | 65140 | LED12DP3LS830/35 | 120 | 6 | 4.75 | 750 | 2050 | 3000 | 84 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver | |
| | | 65141 | LED12DP3LS827/20 | 120 | 6 | 4.75 | 740 | 5000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 20° Beam, Silver | |
| | | 65142 | LED12DP3LS827/35 | 120 | 6 | 4.75 | 740 | 2000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver | |
| | | 65134 | LED12DP3LS/FL/TP | 120 | 3 | 3.75 | 740 | 2000 | 2700 | 83 | 22.8 | 25,000 | \$1.45 | ★ | Accent, 35° Beam, Silver | |
| Compact PAR30 Long Neck - Dimming (Convex Cover) | | | | | | | | | | | | | | | | |
| PAR30 MED | 10 | 61924 | LED10DP3LS830/20 | 120 | 6 | 4.75 | 500 | 3720 | 3000 | 80 | 45.7 | 50,000 | \$1.20 | ★ | Accent, 20° Beam, Silver | |
| | | 61925 | LED10DP3LS827/20 | 120 | 6 | 4.75 | 450 | 3450 | 2700 | 80 | 45.7 | 50,000 | \$1.20 | ★ | Accent, 20° Beam, Silver | |
| | | 68014 | LED10DP3LS827/35 | 120 | 6 | 4.75 | 450 | 1240 | 2700 | 80 | 22.8 | 25,000 | \$1.20 | ★ | Accent, 35° Beam, Silver | |
| | | 63027 | LED10DP3L/FL/TP | 120 | 3 | 4.75 | 450 | 1240 | 2700 | 80 | 22.8 | 25,000 | \$1.20 | ★ | Accent, 35° Beam, Silver | |
| Compact PAR30 - Non-Dimming (Convex Cover) | | | | | | | | | | | | | | | | |
| PAR30 MED | 10 | 75376 | LED10DP30/NFL/TP | 120 | 3 | 3.75 | 340 | 1400 | 3000 | 82 | 27.4 | 30,000 | \$1.20 | | Accent, 24° Beam, Silver | |
| | | 75613 | LED10DP30S830/24 | 120 | 6 | 3.75 | 340 | 1400 | 3000 | 82 | 27.4 | 30,000 | \$1.20 | | Accent, 24° Beam, Silver | |
| | | 76144 | LED10DP30S827/24 | 120 | 6 | 3.75 | 320 | 1300 | 2700 | 82 | 27.4 | 30,000 | \$1.20 | | Accent, 24° Beam, Silver | |
| Compact PAR30 Long Neck - Non-Dimming (Convex Cover) | | | | | | | | | | | | | | | | |
| PAR30L MED | 10 | 75377 | LED10DP30L/NFL/TP | 120 | 3 | 4.75 | 340 | 1400 | 3000 | 82 | 27.4 | 30,000 | \$1.20 | | Accent, 24° Beam, Silver | |
| | | 76145 | LED10DP30LS827/24 | 120 | 6 | 4.75 | 320 | 1300 | 2700 | 82 | 27.4 | 30,000 | \$1.20 | | Accent, 24° Beam, Silver | |
| Retail Display Compact PAR30 Long Neck - Non-Dimming (High CRI - Low Glare - Visual Comfort Lens™) | | | | | | | | | | | | | | | | |
| PAR30L MED | 12 | 66050 | LED12P3LS930/25 | 120 | 6 | 4.75 | 660 | 3000 | 3000 | 92 | 22.8 | 25,000 | \$1.45 | ★ | Narrow Flood, 25° Beam, Silver | |
| | | 66051 | LED12P3LS930/40 | 120 | 6 | 4.75 | 660 | 950 | 3000 | 92 | 22.8 | 25,000 | \$1.45 | ★ | Flood, 40° Beam, Silver | |
| | | 66052 | LED12P3LS927/25 | 120 | 6 | 4.75 | 630 | 3000 | 2700 | 92 | 22.8 | 25,000 | \$1.45 | ★ | Narrow Flood, 25° Beam, Silver | |
| | | 66053 | LED12P3LS927/40 | 120 | 6 | 4.75 | 630 | 900 | 2700 | 92 | 22.8 | 25,000 | \$1.45 | ★ | Flood, 40° Beam, Silver | |

For additional product and application information, please consult GE's website: gelighting.com/ThinkLED

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® qualified

^ Estimated energy cost per year based on \$0.11 per kWh energy rate and 3 operating hours per day

Note: Product descriptions ending in "TP" indicate a card blister or clamshell package nested in a tray for shelf display.

Cards also designed for hook display.





ecomaginationSM



Product is compliant with material restriction requirements of RoHS

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

energy smart[®] is a registered trademark of GE
ENERGY STAR[®] and the ENERGY STAR[®] logo are registered U.S. marks
© 2012 GE 76221 12/06/2012 Printed in USA