





SUPER PULSE START Long Life (SPL)

Extended Life Lamps





Dia. =	3.5" (90mm)
MOL =	8.3" (211mm)
LCL =	5.0" (127mm)
Base =	Mogul (EX39)

MPL 70W/U/ED28/PS/740 **GENERAL Characteristics ELECTRICAL**

Lamp Type	MH Pulse Start Single Ended
ANSI Code	M98/0
Bulb Shape	ED28
Base Type	Mogul (EX39)
Bulb Finish	Clear
Rated Life	40000 hours
Operating Position	Universal
Dimming	50% Rated Power

PHOTOMETRIC

Initial Lumens	5300
Scotopic Lumens (S/P 1.7)	9000
Lumens Per Watt	76
Lamp Lumen Depreciation (LLD)	.80 (80%) @ 16000 hours
Correlated Color Temperature	4000K
Chromaticity Coordinates (CIE-x,y)	.385 .390
Color Rendering Index (CRI)	68

NOTES

Patent Pending

Recycling Program

Lamp Watts

Lamp Oper. Voltage (Nom.)

SUSTAINABILITY

Lamp performance ratings published in this data sheet are based on operation with approved electronic ballasts. Performance ratings of Universal lamps are based upon vertical (±15°) operation. Minimum Starting Temperature: -40°C/°F. To calculate nighttime Scotopic lumens, multiply the lumen rating by the S/P ratio.


70

85

Smartpac[®] 800-451-2606

PHYSICAL

Bulb Diameter	3.5" (90mm)
Max. Overall Length (MOL)	8.3" (211mm)
Light Center Length (LCL)	5.0" (127mm)
Effective Arc Length	10.2mm
Max. Base Temperature (°C)	210
Max. Bulb Temperature (°C)	400
Socket Pulse Rating (KV)	4
Luminaire Type	Open / Enclosed Rated



THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.

