

enhance



The bright white radiance of GE's LED indoor/outdoor decorative lamps is not just something you see, it's something you feel.

LED indoor/outdoor decorative lamps

GE offers dimmable 2.4-watt UL wet-rated LED lamps that are ideal for your indoor/outdoor decorative lighting application needs.

LOW-COST OPERATION

- For example, using only 2.4 watts of energy, save over \$20 in energy costs over the rated life of the lamp versus a standard 15-watt incandescent based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80

COLOR TEMPERATURE

- Halogen-like color
- Available in 3000K and 4000K

LONG LIFE

- Up to 15,000 hours rated life (L70)

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM





imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED indoor/outdoor decorative lamps

Decorative Lamps (Indoor/Outdoor)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Equivalent | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|-------|------------|------------------|------------------|------------|----------|----------------|------|--------------------|-----|--------------------|-----------------------|----------|---------------------|--------------------------|--------------------------|
| Note: 15-watt incandescent replacements (based on ENERGY STAR® requirements for lumens) | | | | | | | | | | | | | | | | | |
|  | CA11 | MED | 2.4 | 65541 | LED2CAM-IO-830/F | 120 | 48/6** | 3.8 | 100 | 3000 | 80 | 15W | 15,000 | - | ★ | Wet | Clear, Fluted, Blunt tip |
| | | | | 65539 | LED2CAM-IO-840/F | 120 | 48/6** | 3.8 | 100 | 4000 | 80 | 15W | 15,000 | - | ★ | Wet | Clear, Fluted, Blunt tip |
| | CAND | 2.4 | 65542 | LED2CAC-IO-830/F | 120 | 48/6** | 3.8 | 100 | 3000 | 80 | 15W | 15,000 | - | ★ | Wet | Clear, Fluted, Blunt tip | |
| | | | | 65540 | LED2CAC-IO-840/F | 120 | 48/6** | 3.8 | 100 | 4000 | 80 | 15W | 15,000 | - | ★ | Wet | Clear, Fluted, Blunt tip |
| S14 Shape | | | | | | | | | | | | | | | | | |
|  | S14 | MED | 2.4 | 65545 | LED2S14-IO/830/F | 120 | 48/6** | 3.4 | 100 | 3000 | 80 | 15W | 15,000 | - | | Wet | Frosted |
| | | | | 65546 | LED2S14-IO/830/C | 120 | 48/6** | 3.4 | 100 | 3000 | 80 | 15W | 15,000 | - | | Wet | Clear |
| | | | | 65543 | LED2S14-IO/840/F | 120 | 48/6** | 3.4 | 100 | 4000 | 80 | 15W | 15,000 | - | | Wet | Frosted |
| | | | | 65544 | LED2S14-IO/840/C | 120 | 48/6** | 3.4 | 100 | 4000 | 80 | 15W | 15,000 | - | | Wet | Clear |

Get more information at
GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: Certified as meeting ENERGY STAR® guidelines.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Incandescent or Halogen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type

Notes: 1) Product descriptions ending in "JTP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



ecomaginationSM

Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2014 GE.

68006 (Rev 8/26/14)