GE Lighting

highlight

The bright white radiance of the GE's LED GU10 lamps isn't just something you see, it's something you feel.

LED GU10 lamps

For decorative lighting applications, GE's dimmable 1, 4, 4.5, 6-watt LED GU10 lamps offer the ideal solution.

LOW-COST OPERATION

- For example, using only 4.5 watts of energy, save over \$83 in energy costs over the rated life of a lamp versus a standard 35-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

• Available with a CRI of 70 - 83

COLOR TEMPERATURE

• Available in 3000K, 3050K and 5500K

LONG LIFE

• Up to 25,000 hours rated life (L70)

DIMMABLE

• Dims from 100% to 10%

BEAM PATTERNS

• Available in 25° beam patterns

ENVIRONMENTALLY CONSCIOUS

• These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

• 3-year limited warranty

To learn more about saving money and energy, go to: **gelighting.com/ThinkLED**

When you Think LED lighting, Think GE.

ecomagination[™]



imagination at work

LED GU10 lamps Directional Lamps (MR16)

| Bulb Shape 120 Volt | Base Type GU10 | Watts | Order Code | Description | Volts | Case Qty" | MOL (In) | Lumens Initial | СВСР | Initial Color Temp | CRI | Wattage Equivalent | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | | Additional Information |
|---------------------------|----------------------|-------|---------------|------------------|-------|--------------|-------------|-------------------|------|--------------------------|-----|-----------------------|-----------------------------|----------|---------------------------|-----|---------------------------|
| MR16 | GU10 | 1 | 73153 | LED1GU10/NFL/CD | 120 | 3 | 2.30 | 35 | 100 | 5500 | 70 | | 12,000 | - | | Dry | Deco Light |
| WILL | | 4 | 75625 | LED4GU10/NFL/CD | 120 | 3 | 2.30 | 100 | 250 | 3050 | 82 | | 15,000 | - | | Dry | Accent, 25° beam, Silver |
| 9 | | 4.5 | 64887 | LED5GU10S830/25 | 120 | 6 | 2.30 | 200 | 800 | 3000 | 82 | 35W | 25,000 | - | \star | Dry | Accent, 25° beam, Silver |
| | | | 66137 | LED4DGU10/NFL/TP | 120 | 3 | 2.30 | 180 | | 3000 | 80 | 25W | 25,000 | Yes | | Dry | Accent, 25° beam, Silver |
| | | 6 | 71240 | LED6DGU10/NFL/TP | 120 | 3 | 2.30 | 340 | 1280 | 3000 | 83 | 35W | 25,000 | Yes | \star | Dry | Accent, 25° beam, Silver |

Get more information at

GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
★ INERGY STAR® status: Certified as meeting ENERGY STAR® guidelines.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, ond includes partially protected locations.
Location, damp – Exterior or interior location that is normally or periodically subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
^ Incondescent or Hologen wattage equivalencies based on ENERGY STAR® guidelines using lumers or CBCP according to lamp type
Notes: 1) Product descriptions ending in "Pri indicate a carded bister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900





Product is compliant with material restriction requirements of RoHS ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks

ecomagination™



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2014 GE.

63556 (Rev 8/26/14)