

The bright white radiance of the GE's LED GU10 lamps isn't just something you see, it's something you feel.

# **LED** GU10 lamps

For decorative lighting applications, GE's dimmable 1, 4, 4.5, 6-watt LED GU10 lamps offer the ideal solution.

#### **LOW-COST OPERATION**

- For example, using only 4.5 watts of energy, save over \$83 in energy costs over the rated life of a lamp versus a standard 35-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

#### **EXCELLENT COLOR RENDERING**

• Available with a CRI of 70 - 83

### **COLOR TEMPERATURE**

• Available in 3000K, 3050K and 5500K

#### **LONG LIFE**

• Up to 25,000 hours rated life (L70)

#### **DIMMABLE**

• Dims from 100% to 10%

#### **BEAM PATTERNS**

• Available in 25° beam patterns

#### **ENVIRONMENTALLY CONSCIOUS**

 These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

## **GE QUALITY AND RELIABILITY**

• 3-year limited warranty

To learn more about saving money and energy, go to: **gelighting.com/ThinkLED** 

When you Think LED lighting, Think GE.

**ecomagination**™



# **LED GU10 lamps**

**Directional Lamps (MR16)** 

Bulb Shape 120 Volt	Base Type GU10	Watts	Order Code	Description	Volts	Case Qty"	MOL (In)	Lumens Initial	СВСР	Initial Color Temp	CRI	Wattage Equivalent	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status		Additional Information
MR16	GU10	1	73153	LED1GU10/NFL/CD	120	3	2.30	35	100	5500	70		12,000	-		Dry	Deco Light
WILL		4	75625	LED4GU10/NFL/CD	120	3	2.30	100	250	3050	82		15,000	-		Dry	Accent, 25° beam, Silver
Ġ.		4.5	64887	LED5GU10S830/25	120	6	2.30	200	800	3000	82	35W	25,000	-	*	Dry	Accent, 25° beam, Silver
			66137	LED4DGU10/NFL/TP	120	3	2.30	180		3000	80	25W	25,000	Yes		Dry	Accent, 25° beam, Silver
		6	71240	LED6DGU10/NFL/TP	120	3	2.30	340	1280	3000	83	35W	25,000	Yes	*	Dry	Accent, 25° beam, Silver

#### Get more information at

# **GELighting.com/ThinkLED**

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

- \*The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

- \* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

  \*\*NERGY STAR®-status: Certified as meeting ENERGY STAR® guidelines.

  # UL 1935 Environmental Requirements for LED LAMPS

  Location, damp Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

  Location, damp Exterior or interior location that is normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

  Location, wet Location in which water or other liquid can drip, splosh, or flow on or against electrical equipment.

  ^Incandescent or Hologen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type

  Notes: 1) Product descriptions ending in "7" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

  2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900





Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks



**ecomagination**™

# www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2014 GE.