



FIELD OR FACTORY INSTALLABLE

## HOTSPOTI LED EMERGENCY LIGHTING KITS FOR T8 LED TUBE RETROFITS

- QUICK PLUG-N-PLAY ROOM-SIDE INSTALLATION
- REVOLUTIONARY DESIGN FOR EXTREME VERSATILITY
- UNV AND MANY BATTERY OPTIONS FOR SUPERIOR ADAPTABILITY
- HIGH EFFICIENCY, HIGH LUMEN OUTPUT LEDS FOR COST EFFECTIVENESS

FILTER Trusted worldwide for cost efficient lighting solutions.









FireHorse<sup>™</sup> HotSpot1 kits for troffers are **UL Classified** emergency lighting systems approved for field installation. Each kit includes a FireHorse<sup>™</sup> brand LED driver, a FireHorse<sup>™</sup> brand battery pack, a ThoroLED<sup>™</sup> brand LED module, required hardware, the necessary **UL Classified** label (to secure to the fixture after installation), and complete installation instructions. These emergency kits are independent (not electrically connected) from the normal lumination source.

## **COMMON SPECIFICATIONS**

Input Voltage: 120V-277V (UNV) Classification: cULus Classified (Field-installable) Surge Protection: C62.41 (TVS) Over Current Protection: Fuse Input Current: 0.07A Input Power: <4W Output Voltage: 3.6V Contact Fulham for mounting heights greater than 10'.

Output Short Circuit Protection: Self Resetting PTC Recharge Time Required: 24 hours Battery Type: NiCd 3.6VDC Illumination Time: Minimum 90 minutes Output Classification: UL 1310 / Class 2 Ambient Temperature: 0°C - 50°C Standard 5 Year Warranty

## HOTSPOT1 KIT MODELS

(500 lumen output recommended for clear and prismatic lenses; higher output for frosted/translucent lenses)

F-cell battery

Model	Watts	Lumen Output	<b>Estimated Run Time</b>	Array Type	<b>Array Dimensions</b>
FHSKITT04LNC	4	500	145 Mins	Linear	L 4.68", W .82"
FHSKITT04LND	4	500	200 Mins	Linear	L 4.68", W .82"
FHSKITT04LNF	4	500	360 Mins	Linear	L 4.68", W .82"
FHSKITT06SHC	6	750	90 Mins	Small-H	L 3.54", W 3.93"
FHSKITT06SHD	6	750	125 Mins	Small-H	L 3.54", W 3.93"
FHSKITT06SHF	6	750	235 Mins	Small-H	L 3.54", W 3.93"
FHSKITT08LHD	8	1000	90 Mins	Large-H	L 5.71", W 3.93"
FHSKITT08LHF	8	1000	175 Mins	Large-H	L 5.71", W 3.93"
FHSKITT10LHF	10	1250	135 Mins	Large-H	L 5.71", W 3.93"
FHSKITT10SHF	10	1250	135 Mins	Small-H	L 3.54", W 3.93"
PART # EXAMPLE:	FHS	КІТ	T 10 LH	F	

Troffer

Watts

Large H-model

FUTBER. Trusted worldwide for cost efficient lighting solutions.

FireHorse HotSpot

Kit

