

# MasterColor CDM ED17 Protected

MasterColor CDM 70W/930 P CO U ELITE

Direct retrofit with immediate energy savings! Range of protected, high-efficiency long life ceramic metal halide lamps with a stable color over lifetime and a crisp, sparkling light to be used in open fixtures.



## Product data

### • General Characteristics

Base	Medium [Single Contact Medium Screw]
Base Information	Brass [Brass Base]
Bulb	ED17P [Protected]
Bulb Material	Hard Glass
Bulb Finish	Coated
Operating Position	Universal [Any or Universal (U)]
Main Application	General and Street Lighting
RatedAvgLife(See Family Notes)	16000 hr

Lamp Voltage	100 V
Lamp Current	0.92 A
Ignition Time	10 (max) s
Re-ignition Time [min]	8 (max) min

### • Environmental Characteristics

Mercury (Hg) Content	7.6 (max) mg
Picogram per Lumen Hour	88.6 p/LuHr

### • Light Technical Characteristics

Color Code	930 [CCT of 3000K]
Color Rendering Index	87 (min), 90 (nom) Ra8
Color Designation	Warm White
Color Temperature	2900 K
Color Temperature technical	2900 K
Initial Lumens	6100 Lm
Luminous Efficacy Lamp	87 Lm/W
Lumen Maintenance - 10% life	95 %
Lumen Maintenance - 40% life	90 %
Design Mean Lumens	5800 Lm
Chromaticity Coordinate X	0.436 (min), 0.445 (nom), 0.454 (max)
Chromaticity Coordinate Y	0.391 (min), 0.397 (nom), 0.403 (max)

### • UV-related Characteristics

Damage Factor D/fc	0.14 -
PET (NIOSH)	1045 h500lx
UV A	3.7 mW/cm <sup>2</sup>
UV B	0 mW/cm <sup>2</sup>
UV C	0 mW/cm <sup>2</sup>

### • Luminaire Design Requirements

Cap-Base Temperature	190 (max) C
Bulb Temperature	400 (max) C

### • Product Dimensions

Light Center Length L	3.39 in
Max Overall Length (MOL) - C	5.438 (max) in
Diameter D	2.125 in

### • Electrical Characteristics

Watts	70 W
-------	------

**PHILIPS**

• Footnotes

Footnotes HID 902 [Exclusive to Philips Lighting Company.]

• Product Data

Product number 423699  
 Full product name MasterColor CDM 70W/930 P CO U ELITE


Short product name MHC70/C/U/MP/3K ELITE  
 Pieces per Sku 1  
 eop\_pck\_cfg 12  
 Skus/Case 12  
 Bar code on pack 46677423698  
 Bar code on case 50046677423693  
 Logistics code(s) 928601173901  
 eop\_net\_weight\_pp 0.001 kg

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will

remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Dimensional drawing



MasterColor CDM 70W/930 P CO U ELITE

Product	C (Max)	D (Norm)
MHC P 70W/930 E26 ED17P CO U ELITE	5.438	2.125



E26



© 2014 Koninklijke Philips N.V. (Royal Philips)  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2014, August 2  
data subject to change