

Reflector Flood

Reflector 65W 120V BR30 FL 1CT



Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These flood lamps produce homogeneous beams of high intensity for general illumination.

Product data

• General Characteristics

Base	Medium [Single Contact Medium Screw]
Base Information	Aluminum [Aluminum Base]
Bulb	BR30
Bulb Finish	Frosted
Filament Shape	CC6 [Straight]
Operating Position	Universal [Any or Universal (U)]
Main Application	Indoor Reflector
Atmosphere	Gas
Life with 3h/day use [years]	1.8 an
Estimated Energy Cost/YR	7.83 \$

• Light Technical Characteristics

Beam Description	Flood [Flood]
Beam Angle	55 D
Color Temperature	2710 K
Initial lumen	620 Lm

• Electrical Characteristics

Watts	65 W
Voltage	120 V

• Product Dimensions

Max Overall Length (MOL) - C	5.375 (max) in
------------------------------	----------------

Diameter D 3.75 in

• Footnotes

Footnotes Incandescent	905 [Consider the compact fluorescent lamps for energy savings.]
Footnotes Incandescent	87 [Do not allow hot bulb to come in contact with liquid or metal parts of the fixture, as glass may shatter. Do not use outdoors. Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. (87)]


• Product Data

Product number	248765
Full product name	Reflector 65W 120V BR30 FL 1CT
Short product name	Refl 65W 120V BR30 FL 1CT
Pieces per Sku	1
eop_pck_cfg	12
Skus/Case	12
Bar code on pack	46677225193
Bar code on case	50046677225198
Logistics code(s)	920681036369
eop_net_weight_pp	0.052 kg

PHILIPS

Reflector Flood

Dimensional drawing



E26

Reflector 65W 120V BR30 FL 1CT

