

Project			
Catalog			

Type

## **DESCRIPTION**

The newest addition to the MAXCOR Downlight Family from NICOR, the DEB6 is the perfect LED downlight for wall lighting and sloped ceilings. With a 360°/30° range of motion the DEB6 provides the flexibility for those applications where the standard DLR56 doesn't quite fit. The DEB6 gives you the ability to aim over 1200 lumens of warm, 3000K, incandescent-like light exactly where it's needed.

## **FEATURES AND SPECIFICATIONS**

>1200 Lumens

30° adjustability for wall lighting and slope ceiling

Compatible with most 6" recessed housings

50,000 hour life expectancy

Easy installation with adjustable torsion springs

Dimmable to 10% with most dimmers

Wet location rated

Suitable for use in IC Rated recessed housings

5 year warranty

Complete warranty details can be found at:

http://nicorlighting.com/resources/warranty-info/maxcor-brand-limited-warranty

## **PRODUCT INFORMATION**

 LED Lifetime (Hrs):
 50,000


 Input Voltage (V)
 120V

 Power Draw (W)
 18.6W

Fixture Height 4.125" (104.8 mm)

Trim Width: 7.5" (190.5 mm)





Ordering Information Example: DEB6-10-120V-3K-WH				
Series	Version	Voltage	CCT's	Trim Color
DEB6	<b>10</b> (1)	120V	<b>3K</b> (3000)	<b>WH</b> (white)











## **Photometric Data -** *Type C Gonio Photometer*

3000K Product Specifications						
Luminaire	Input Voltage (VAC)	System Level Power (W)	Delivered Lumens (Lm)	System Efficacy (Lm/W)	Correlated Color Temp (K)	Color Ren- dering Index (CRI)
3000 K	120	18.6	1256	67.4	3030	82

3000K Zonal Lumen Summary					
Zone (Degrees)	Lumens	% of Luminaire			
0-30	428	34.10%			
0-40	673	53.60%			
0-60	1081	86.04%			
0-90	1256	100.00%			
90-180	0	0.00%			
0-180	1256	100.00%			

