

Dimmable CFL & LED bulbs

Compatible with Lutron 100W & 150W C-L® dimmers



This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

For more information

If you'd like more information regarding bulb performance and test results, including dimming range, other dimmer options, and performance, please visit www.lutron.com/ledtool.

Warranty on your Lutron 100W C•L dimmer or 150W C•L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.

Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|----------|---------------------|----------------------------|--|
| Cree | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | CR4-575L | 4" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 13.5W | BA19-08027OMN-12DE26-1U100 | A19, Soft White, 2700K, 800 Lumen, E26, 13.5W |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| Ecosmart | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS 20 CW FL 50WE 120 | PAR20, 5000K, 490 Lumen |
| | 8W | ECS 20 WW FL 50WE 120 | PAR20, 3000K, 450 Lumen |
| | 9.5W | ECO4-575L | 4" Downlight, 2700K, Medium Base |
| | 9.5W | ECO4-575L-50K | 4" Downlight, 5000K, Medium Base |
| | 9.5W | ECO4-575L-50K-GU24 | 4" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | ECO-575L-50K-GU24 | 6" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 10W | ECS BR30 65WE WW 120 DG | BR30, Warm White, 3000K, 650 Lumen, E26 |
| | 10.5W | ECS 30 75WE XXX GB XX 120 | PAR30, various color temperatures |
| | 11.5W | ECS BR30 65WE CW 120 | BR30, 5000K, Medium Base |
| | 11.5W | ECS BR30 65WE W27 120 | BR30, 2700K, 650 Lumen, Medium Base |
| | 14W | ECS BR40 90WE CW 120 DG | BR40, Daylight, 5000K, 1050 Lumen, E26 |
| | 15W | ECS BR30 W27 FL 120 | BR30, Soft White, 2700K |
| 24W | ECS 38 V2 WW FL 120 | PAR38, Warm White, 3000K | |
| Feit | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 5W | MR16/GU10/DM/LED† | MR16, GU10 Base |
| | 6.5W | BPMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | R16DM/LED† | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|------------------|---------|-----------------------------|--|
| Feit | 7.5W | PAR20DM/5K/LED [†] | PAR20, 5000K |
| | 7.5W | PAR20DM/LED [†] | PAR20, 3000K |
| | 8W | BPCER20/DM/LED | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| | 17W | BR40/DM/LED [†] | BR40, 2700K, 1065 Lumen |
| | 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen |
| GE | 8W | LED8DA19/827 | A19, 2700K, 450 Lumen, E26 |
| | 14W | LED14DA21V2/827W | A21, 2700K, 1100 Lumen, E26 |
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| | 10.5W | LS 30 75WE XXX GB XX 120 | PAR30, various color temperatures |
| | 11.5W | DFN BR30 65WE CW 120 | BR30, Cool White, 5000K, Medium base |
| | 11.5W | DFN BR30 65WE NW 120 | BR30, Neutral White, 4000K, Medium base |
| | 11.5W | DFN BR30 65WE W27 120 | BR30, Warm White, 2700K, Medium base |
| | 11.5W | DFN BR30 65WE WW 120 | BR30, Warm White, 3000K, Medium base |
| | 13W | LS GLP6 W27 120 WH S1 BX | 6" Downlight, 2700K, E26 retrofit |
| | 15W | DFN BR30 CW FL 120 | BR30, Cool White, 5000K |
| | 15W | DFN BR30 NW FL 120 | BR30, Neutral White, 4000K |
| | 15W | DFN BR30 W27 FL 120 | BR30, Warm White, 2700K |
| | 15W | DFN BR30 WW FL 120 | BR30, Warm White, 3000K |
| | 24W | DFN 38 CW V2 FL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 CW V2 NFL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 NW V2 FL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 NW V2 NFL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 W27 V2 FL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 W27 V2 NFL 120 | PAR38, Warm White, 2700K |

[†] Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|------------------|---------|---------------------------------------|--|
| Lighting Science | 24W | DFN 38 WW V2 FL 120 | PAR38, Warm White, 3000K |
| | 24W | DFN 38 WW V2 NFL 120 | PAR38, Warm White, 3000K |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| Philips | 4W | 9290002120 | MR16, Bright White, 3000K, 200 Lumen, GU10, 4W |
| | 4.5W | 9290002439 | Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light |
| | 7W | 9290002706 | A19 Slim Style, Daylight, 5000K, 450 Lumen, E26 |
| | 8W | 9290002267 | A19, 2700K, 478 Lumen |
| | 8W | 9290002295 | A19, 5000K |
| | 8.5W | 9290002543 | BR30, 5000K, 730 LUMEN, 8.5W |
| | 10.5W | 9290002544 | BR30, 2700K, 730 LUMEN, 8.5W |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |
| | 13W | 9290002233 | PAR30, 2700K, 784 Lumen |
| | 13W | 9290002234 | PAR30, 2700K, 770 Lumen |
| | 13W | 9290002201 | PAR30, 3000K, 804 Lumen |
| | 13W | 9290002323 | PAR30 |
| | 13W | 9290002523 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 832 Lumen |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26, 19W |
| | 17W | 9290002018† | A21, 2700K |
| | 17W | 17E26A21D† | A21, 2700K |
| | 18W | 9290002202 | PAR38, 3000K, 951 Lumen, Medium Base |
| | 18W | 9290002236 | PAR38 |
| | 18W | 9290002237 | PAR38 |
| | 18W | 9290002245 | PAR38, 2700K, 938 Lumen |
| | 18W | 9290002246 | PAR38 |
| | 18W | 9290002307 | PAR38 |
| | 18W | 9290002308 | PAR38 |
| | 18W | 9290002309 | PAR38 |

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|----------------|---------------------|-------------------------------|--|
| Philips | 18W | 9290002310 | PAR38 |
| | 18W | 9290002311 | PAR38 |
| | 18W | 18E26PAR38-3 | PAR38 |
| | 18W | 18E26PAR38-4 | PAR38 |
| Samsung | 7W | STIPLW8300711AB | SI-P8V071AB0US |
| Satco | 11W | S9084 | PAR30, 3000k, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9086 | PAR30, 3000k, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| 28W | LR38/40/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 | |
| 28W | LR38/40/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|--------|---------|---------------------|---|
| Solais | 7W | LRP20/25/27K | PAR20, 2700K, 475 Lumen, E26, 25° Beam |
| | 7W | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| | 7W | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam |
| | 7W | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam |
| | 11W | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood |
| | 11W | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood |
| | 11W | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood |
| | 11W | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood |
| | 16W | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |
| | 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|------------------|---------------------------|--------------------------------|---|
| Solais | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Sylvania | 8W | LED8A/DIM/F/827 | A19, 2700K |
| | 8W | LED8A/DIM/F/830 | A19, 3000K |
| | 8W | LED8PAR16/DIM/930/FL36/P/LW | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/FP | PAR16, GU10, Soft White, 390 Lumen |
| | 9W | LED/550/RT4/827/FL80/WRFL | 4" Downlight, 2700K |
| | 9W | LED/550/RT4/830/FL80/WRFL | 4" Downlight, 3000K |
| | 11W | LED11PAR20/DIM/930/FL30/P2 | PAR20, Soft White, 550 Lumen |
| | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| | 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot |
| | 17W | LED17PAR30LN/DIM/P/930/NFL25† | PAR30, 3000K, 900 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38 |
| | 21W | LED21/PAR38/DIM/P/930/FL30/HVP | PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W |
| 21W | LED21PAR38/DIM/P/930/FL30 | PAR38, 3000K, 1100 Lumen | |
| Utilitech | 3W | LG161/2DM/IF/LED† | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LCFCDM/300/LED† | Candle, Warm White, 3000K, 300 Lumen, E12 base, clear flame tip |
| | 4.8W | LCFFDM/300/LED† | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|--------------|--------------|-------------------------|--|
| Utilitech | 4.8W | LEFCDM/300/LED† | Candle, Warm White, 3000K, 300 Lumen, E26 base, clear flame tip |
| | 4.8W | LG161/2DM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LG161/2DM/IF/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 5W | LMR16GU10DM/LED† | MR16, GU10 Base |
| | 6.5W | LMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | LMR16DMGU10† | MR16, GU10 base |
| | 6.5W | LR16DMLED† | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | LPAR20DM/5K/LED† | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED† | PAR20, 3000K |
| | 8W | LR20DMLEDG2 | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 11W | DLS02-41127D1E-WF1 | 4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit |
| | 13W | DLS02-61327D1E-WF1 | 5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit |
| | 13W | DLS02-61350D1E-WF1 | 5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit |
| | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | 16W | LBR40DMLEDG2† | BR40, 2700K, 1065 Lumen |
| | 17W | BPCEBR40/DM/LED† | BR40 |
| 17W | LBR40DM/LED† | BR40, 2700K, 1065 Lumen | |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Caséta Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------|---------|------------------|--------------------|
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |
| | 14W | 4R2014TD | R20, TruDim, 2700K |
| TCP | 14W | 4R2014TD30K | R20, TruDim, 3000K |
| | 14W | 4R2014TD35K | R20, TruDim, 3500K |
| | 14W | 4R2014TD41K | R20, TruDim, 4100K |
| | 14W | 4R2014TD50K | R20, TruDim, 5000K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model number | Description |
|----------|---------|----------------------------|---|
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 13.5W | BA19-08027OMN-12DE26-1U100 | A19, Soft White, 2700K, 800 Lumen, E26, 13.5W |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| Ecosmart | 7W | ECS 25 40WE W27 120 | G25, Warm White, 2700K |
| | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| Feit | 7.5W | PAR20DM/5K/LED† | PAR20, 5000K |
| | 7.5W | PAR20DM/LED† | PAR20, 3000K |
| | 9.5W | BPCER20/DM/LED | PAR20 |
| | 9.5W | PAR20/5K/LEDG5 | PAR20, 5000K |
| | 9.5W | PAR20/5K/LEDG5/CAN | PAR20, 5000K |
| | 9.5W | PAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | PAR20/LEDG5/CAN | PAR20 |
| | 10W | G25/DM/LED | G25, 3000K |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| GE | 18W | LED18D38W827/15 | PAR38, 2700K, E26, 15° Beam |
| | 18W | LED18D38W827/25 | PAR38, 2700K, E26, 25° Beam |
| | 18W | LED18D38W827/40 | PAR38, 2700K, E26, 40° Beam |
| | 18W | LED18D38W830/15 | PAR38, 3000K, 1400 Lumen, E26, 15° Beam |
| | 18W | LED18D38W830/25 | PAR38, 3000K, 1400 Lumen, E26, 25° Beam |
| | 18W | LED18D38W830/40 | PAR38, 3000K, 1400 Lumen, E26, 40° Beam |
| | 18W | LED18D38W927/15 | PAR38, 2700K, 1100 Lumen, E26, 15° Beam |
| | 18W | LED18D38W927/25 | PAR38, 2700K, 1100 Lumen, E26, 25° Beam |
| | 18W | LED18D38W927/40 | PAR38, 2700K, 1100 Lumen, E26, 40° Beam |
| | 18W | LED18D38W930/15 | PAR38, 3000K, 1200 Lumen, E26, 15° Beam |

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model number | Description |
|------------------|--------------|------------------------------|--|
| GE | 18W | LED18D38W930/25 | PAR38, 3000K, 1200 Lumen, E26, 25° Beam |
| | 18W | LED18D38W930/40 | PAR38, 3000K, 1200 Lumen, E26, 40° Beam |
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| Philips | 8W | 9290002267 | A19, 2700K, 478 Lumen |
| | 8W | 9290002295 | A19, 5000K |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 832 Lumen |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26, 19W |
| | 17W | 9290002018 | A21, 2700K |
| Samsung | 7W | STIPLW8300711AB | SI-P8V071ABOUS |
| | 10.5W | S9037 | A19, 2700K, 810 Lumen, E26 |
| Satco | 10.5W | S9038 | A19, 3500K, 830 Lumen, E26 |
| | 10.5W | S9039 | A19, 5000K, 870 Lumen, E26 |
| | 8W | LED8A/DIM/F/827 | A19, 2700K |
| Sylvania | 8W | LED8A/DIM/F/830 | A19, 3000K |
| | 7.5W | LA19DM/LEDG2 | A19, 3000K, 450 Lumen |
| Utilitech | 7.5W | LPAR20DM/5K/LED [†] | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED [†] | PAR20, 3000K |
| | 9.5W | LPAR20/5K/LEDG5 | PAR20, 5000K, 500 Lumen |
| | 9.5W | LPAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 10W | LG25/DM/LED | G25, 3000K |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | Westinghouse | 8W | 8A19/LED/DIM/30 |
| 8W | | 8A19/LED/DIM/50 | A19, Cool White, 5000K |

[†] Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model | Description |
|-------|---------|------------------|-------------|
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |

* CFLs typically require a warmup period before their full dimming range is achieved.