



DATA SHEET

PATYK Floor lamp

Product characteristics

PATYK Floor lamp is composed of an MDF Veneer base and PDS-O Fixture: high quality, double anodized aluminum PDS-O extrusion, LEDs and the option of no switch, Micro Switch or Proximity Switch. LED features: high light efficiency and effectiveness, consistent color tone and low power consumption. LEDs are covered by a frosted Liger cover which allows a line of light without dots. The PDS-O Fixture is not permanently mounted to the base and is inserted into a special connector; as a result the fixture can be taken out of the base at any time and can be rotated into any direction. Additionally, the fixture can be easily exchanged for another one with different LEDs without the need of exchanging the whole lamp. Low voltage power runs through the DC jack 2.1/5.5mm that is located in the base of the lamp.

Applications

The Floor Lamp has a unique look and innovative construction and as a result it fits contemporary interiors. Energy efficient LEDs make the product inexpensive in use and at the same time effectively lighting a living space.

Technical specification

Nominal voltage	120V (12V DC supplied by an included 120V to 12V wall plug transformer)
Light source	LED
Fixture power	14.4W
Correlated Color Temperature (CCT)	4100 K (CW – cool white)
Color Rendering Index (CRI)	80+
Ingress Protection Rating	IP 20
Protection Class	III
Dimensions	diameter – 24 cm, height – 150 cm
Material	base – MDF, extrusion – aluminum, cover – polycarbonate (PC)
Connector	socket DC 2.1/5.5