

# PAR30L 25°

# LED

## 10.5 Watt PAR30L Specifications



The ETi 10.5 watt PAR30L LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Integrated optical reflectors provides high quality point source beam versus pixilated designs. They are UL listed for use in dry locations and are RoHS compliant with no lead or mercury. Warranty is 3 years or 36 months. Suitable for installations from -4° F to 104° F.


### KEY FEATURES & BENEFITS

- 10.5 Watt Low Power and High Performance
- 525 Lumen
- Dimmable
- 81 CRI
- 3000K
- Replaces most applications using 50w incandescent lamps
- Rated Lifetime: 40,000 hours



This light source meets restrictions on hazardous substances.

### LAMP DIMENSIONS



SKU# 520256  
Dimension A = 3.74"  
Dimension B = 4.50"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see [www.etiled.us](http://www.etiled.us)

### APPLICATION INFORMATION

Indoor recessed can, high hat, ceiling mounted strip lighting and outdoor flood lighting applications in residential, office, retail, restaurant, school, hospital and hotel/motel locations.

**ETi** SOLID STATE™  
LIGHTING  
INC.

# 10.5 Watt PAR30L

# LED

## SPECIFICATION DATA

Project \_\_\_\_\_

Item Number \_\_\_\_\_

Prepared by \_\_\_\_\_ Date \_\_\_\_\_

## ORDERING INFORMATION

Item Number	Description	Wattage	Base Type	Input Voltage (VAC)	Average Rated Life <sup>1</sup>	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CBCP	Beam	R9	Duv	CRI <sup>4</sup>	Power Factor	Operating Frequency
520256	PAR30L 10.5 E26 DIM E83025	10.5	E26	120	40,000	525	3000K	2550	25°	15	-0.0027	81	>0.9	60Hz
<sup>1</sup> Hours lifetime with 70% lumen maintenance														
<sup>2</sup> Thermally stable typical lumens (±10%)														
<sup>3</sup> Thermally stable CCT (±10%)														
<sup>4</sup> Color rendering index/Ra														

## SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
520256	8366070 07308	5.2" x 4.0" x 4.0"	.6	n/a	n/a	n/a	n/a	12	30836607 007309	11.5" x 12.8" x 8.7"	8.3

