

# MR16 GU10

# LED

## 7w MR16 GU10 Specifications



The ETi 7W MR16 GU10 LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Lasting over 10 times longer, these MR16 lamps are high quality replacements for incandescent lamps and is available in 2700°K. They are UL listed for use in damp and dry locations and are RoHS compliant with no lead or mercury. Warranty is 3 years or 36 months. Suitable for installations from - 4° F to 104°


### KEY FEATURES & BENEFITS

- 7 Watt Low Power and High Performance
- 360 Lumen
- Dimmable
- 81 CRI
- 2700K
- UL- Damp and Dry locations
- Replaces most applications using 35w energy saving incandescent lamps
- Rated Lifetime: 25,000 hours



This light source meets restrictions on hazardous substances.

### LAMP DIMENSIONS



SKU# 53202113

Dimension A = 1.95"

Dimension B = 2.3"

Dimension C = .86"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see [www.etiled.us](http://www.etiled.us).

### APPLICATION INFORMATION

Wall washing, down lighting, accent lighting and general decorative indoor lighting in residential, office, retail, restaurant, school, hospital and hotel/motel locations.

**ETI** SOLID STATE™  
LIGHTING  
INC.

# MR16 GU10

# LED

## SPECIFICATION DATA

Project \_\_\_\_\_

Item Number \_\_\_\_\_

Prepared by \_\_\_\_\_ Date \_\_\_\_\_

## ORDERING INFORMATION

Item Number	Description	Wattage	Base Type	Input Voltage (VAC)	Average Rated Life <sup>1</sup>	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CBCP	Beam	CRI <sup>4</sup>	R9	Duv	Power Factor	Operating Frequency
53202113	MR16 7 GU10 E 82740	7	GU10	120	25,000	360	2700K	612	40°	81	12	0.0008	>0.78	60Hz

<sup>1</sup> Hours lifetime with 70% lumen maintenance

<sup>2</sup> Thermally stable typical lumens (±10%)

<sup>3</sup> Thermally stable CCT (±10%)

<sup>4</sup> Color rendering index/Ra

## SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Carton Dimensions (H x L x W)	Master Pack Weight (lbs)
53202113	836607 008596	2.6" x 2.2" x 2.2"	.19	12	30836607 008597	5.6" x 6.9" x 4.7"	2.4	48	50836607 008591	12.3" x 10.1" x 7.6"	10.4

