G25 LED

7 Watt G25 Specifications



The ETi 7 watt 500 lumen G25 LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. They are UL listed for use in damp and dry locations and are RoHS compliant with no lead or mercury. Warranty period is 3 years or 36 months. Suitable for installations from – 4° F to 113° F.

KEY FEATURES & BENEFITS

- 7 Watt Low Power and High Performance
- 500 Lumen
- Dimmable
- 82 CRI
- 3000K
- UL Damp or Dry Locations
- Replaces most applications using 60w energy saving incandescent lamps

Rated Lifetime: 25,000 hours










LAMP DIMENSIONS



SKU# 52028111

Dimension A = 3.2" Dimension B = 4.3"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us

APPLICATION INFORMATION

Chandeliers, bathroom vanity, accent lighting and general decorative indoor

lighting in residential, office, retail, restaurant, school, hospital and hotel/motel locations.





8.5 Watt G25

LED

SPECIFICATION DATA

Project	
Item Number	
Prenared by	Date

ORDERING INFORMATION

ltem Number	Description	Wattage	Base Type	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CBCP	Beam	R9	Duv	CRI⁴	Power Factor	Operating Frequency
52028111	G25 7 E26 DIM E830D164	7	E26	120	25,000	500	3000K	91.2	160	7.2	0.001	82	>0.94	60Hz

¹ Hours lifetime with 70% lumen maintenance

SHIPPING INFORMATION

						Inner Car-	Inner				Master
		Item Di-	Item	Inner	Inner Car-	ton Dimen-	Pack	Master	Master	Master Di-	Pack
Item	Item UPC	mensions	Weight	Pack	ton Bar	sions	Weight	Pack	Carton Bar	mensions	Weight
Number		(HxLxW)	(lbs)	Qty	Code	(HxLxW)	(lbs)	Qty	Code	(H x L x W)	(lbs)
		4.9" x 3.5"			308366070	10.4" x			50836607	21.9" x 14.4"	
52028111	836607006387	x 3.5"	0.33	6	06388	13.7" x 6"	3.8	24	006382	x 12.7"	17.4





² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra