

Retrofit Downlight



4" LED Retrofit Downlight

High Color Rendering Index 90
Suitable for use in wet locations
Equivalent to 60W Incandescent



Product Features



- Fit for 4" Recessed Cans
- Designed for wet locations
- Complying California Title 24 lighting requirements
- Used 12W of energy; equivalent to 60W incandescent
- High Rendering Index at 90
- Available in 2700K and 4000K colors
- 120° Beam angle
- Included E26/GU24 bases
- Dimming range 10%-100%
- Rated life for 40,000 hours
- Instant on- No warm-up period
- No UV/IR light in the beam
- Mercury-Free

Environmental Commitment

- RoHS compliant – Contains no harmful lead or mercury
- Disposable with no environmental risk
- UV and IR free
- UL wet rated

Application

- Used for 4" Recessed down light
- Suitable for use in wet locations such as kitchen, bathroom
- Offices, retails, hospitalities, residential homes and etc

Key Technical Data

Models	CM4DL-7201
Can sizes	4"
Rated Wattage	12W
Luminous Flux	600lm
Wattage Equivalent	60W
Input Voltage	120V @60Hz
Beam Angle	120 °
CRI	>90
CCT options	2700K/4000K
Power Factor	>0.9
Dimming Range	10%-100%
Bases included	E26 and GU24

Packaging Information

Product Net weight	0.55 lbs (0.25kg)
Inner Box quantity	1
Inner box gross weight	0.7 lbs (0.325kg)
Inner box dimension	142×142×97mm
Master carton quantity	12 pcs
Master carton gross weight	10.3 lbs (4.69kg)
Master carton dimension	590×444×218mm

Ordering Information

Model	Wattage	CCT
CM4DL-7201-9XX	12W	XX = 27 for 2700K XX = 40 for 4000K

For example, CM4DL-7201-927 for 12W Downlight with E26 base and optional GU24 connector in 2700K CCT

Dimmer Compatible List

Brands	Models
Lutron	DV-603P 600W
	LGCL-153CL 600W
	TGCL-153PH-WH
	DV-603PR 600W
	S-600PR-WH 600W
Leviton	6631-LA 600W
	IPI06 600W
	S-600P-WH
GE	18024 600W
Almond	LUXDM600-12 600W

Product Dimension

