



PRO



- Omnidirectional: 275° beam angle
- High efficacy 70 LPW in Warm White
- Frosted finish for extra low glare
- Compact heat sink blends in with fixtures
- Energy efficient alternative to incandescent candle lighting
- Smooth dimming with existing installations

















\$112 Savings per lamp\*
























## **SPECIFICATIONS**

Product Model	40730 5B11G4DIM/827/FR
Туре	B11 (candle)
Base	E12
Power (W)	5
Voltage - Frequency	120V 60Hz
Color Temp. (ANSI)	Warm White 2700K
CRI (Ra)	82
Typical lumens (lm)	350
Efficacy (LPW)	70
Beam Angle	275°
Dimmable	Yes**
Power Factor	0.9
Rated Lifetime - L70 (hrs.)	25,000
Dia. x MOL	1.38"x3.90" (35x99mm)
Weight (lb. / g)	0.11lb / 49g

<sup>\*</sup> Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$16 LED with 25,000-hr lifetime \*\* List of tested dimmer switches available on website \*\*\* Not intended for use in totally enclosed fixtures \*\*\*\* Suitable for damp locations. Not for use where directly exposed to weather or water