





F17T8/835 Lamp Specifications

TCP Item Number: 31017835

Lamp code: F17T8/835



Cathode Guarded

Average Rated Life (hours)	
3 hours per start -----	24,000
TCLP Compliant -----	Yes
Mercury Level -----	4.3 mg

Physical Characteristics

Lamp type -----	T8
Base type -----	Med. BiPin (G13)
Lamp Material -----	Soda Lime
Phosphor -----	Tri-Phosphor
Lamp Diameter (inches)	
Nominal (D) -----	1.00
Maximum (D) -----	1.10
Minimum (D) -----	.94
Overall Length (inches)	
Nominal (C) -----	24.00
Maximum (C) -----	23.78
Minimum (C) -----	23.67
Face to Face	
Maximum (B) -----	23.22
Minimum (B) -----	23.12


Photometric Characteristics

Initial Lumens -----	1400
Mean Lumens (40% of rated life) -----	1330
Correlated Color Temperature (Kelvin) -----	3500
Color Rendering Index (CRI) -----	85
Normal Efficacy (Lumens/Watts) -----	82


Electrical Characteristics

Lamp Watts -----	17
Nominal Lamp Volts -----	65
Nominal Lamp Operating Frequency (Hz) -	50-60 Hz
Min. Starting Temperature (Degrees C) ---	10°
Min. Starting Lamp Voltage at 10°C -----	210
Min. Cathode Resistance (Rh/Rc) -----	4.25
Max. Cathode Resistance (Rh/Rc) -----	6.5


Spectral Power Distribution



Lamp Lumen Maintenance



Typical Lamp Mortality



24 MONTH
STANDARD WARRANTY

For the most up-to-date specs, please visit www.tcp.com

TCP is proud to have been awarded
ENERGY STAR® Partner of the Year 2013.

