PAR38 17W DIM. GU24 TITANIUM CRISP LED SERIES 4.0











T24 2013

- Full-face REFINE optic and sleek design
- Exceptional color rendering CRI 90
- Richer reds and natural skin tones (R9 50, R13 90)
- Tight LED binning for consistent CCT across all lamps
- Suitable for use in totally enclosed fixtures
- Wet location rated for outdoor use







Savings per lamp*





















PATENT PENDING REFINE OPTIC

The innovative REFINE optic provides a high candela to lumen ratio, optimizing light usage for directional applications.




WATCH THE VIDEO




ILLUMINANCE & CANDELA DISTRIBUTION

17PAR38G4DIM/927FL40/GU24




Diameter Footcandles					
2.2	267				
4.4	67				
6.6	30				
8.7	17				
10.9	11				




Degree	
0	2400
5	2236
15	1429
25	366
35	138
45	71

17PAR38G4DIM/930FL40/GU24




2.2	278
4.4	69
6.6	31
8.7	17
10.9	11



2500 2329 1489
1.400
1409
381
143
74

Base: **GU24** Voltage: 120V Dimmable: Yes*** PF: 0.9

Lifetime: 40,000 hrs Weight: 0.75lb / 340g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	R9 / R13 (typ.)	Lumens	LPW	Beam Angle	CBCP (cd)
17PAR38G4DIM/927FL40/GU24	16303	17	Warm White 2700K	90	50 / 90	1105	65	FL 40°	2400
17PAR38G4DIM/930FL40/GU24	16306	17	Warm White 3000K	90	50 / 90	1150	68	FL 40°	2500

^{*} Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$8 halogen with 1500-hr lifetime, \$32 LED with 40,000-hr lifetime
** Suitable for use in totally enclosed fixtures
**** List of tested dimmer switches available on website
***** Suitable for wet locations when used in base down applications only