## GE Lighting



The bright white radiance of the GE energy smart<sup>®</sup> LED retail PAR38 lamps is not just something you see, it's something you feel.

# GE energy smart<sup>®</sup> LED retail PAR38 lamps

For superior light in retail spaces, the 17-watt GE energy smart<sup>®</sup> LED retail PAR38 lamp offers the perfect blend of enhanced color quality, advanced optics, and reduced glare.

#### LOW-COST OPERATION

- Using only 17 watts of energy, save over \$236 in energy costs over the rated life of a lamp versus a standard 60-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources
- Our LED PAR lamps have less heat, UV or infrared in the beam, which reduces the potential for fading of materials and décor, compared to halogen or incandescent lamps

#### **EXCELLENT COLOR RENDERING**

• Available with a CRI of 82 to 92

#### **COLOR TEMPERATURE**

Halogen-like color
Available in 2700K and 3000K



### **ecomagination**<sup>™</sup>

#### LONG LIFE

- 25,000 hours rated life (L70) for 14- and 18-watt retail PAR38
- 50,000 hours rated life (L70) for 17-watt retail PAR38

#### **BEAM PATTERNS**

 $\bullet$  Available in 15°, 17°, 25° and 40° beam patterns

#### ENVIRONMENTALLY CONSCIOUS

• These lamps are energy efficient, contain no lead or mercury, and are RoHS compliant

#### **GE QUALITY AND RELIABILITY**

• 3-year limited warranty

Featuring GE's exclusive **Visual Comfort Lens**<sup>™</sup> for the perfect blend of enhanced color quality, advanced optics and reduced glare. Exclusive Visual Comfort Lens<sup>™</sup> Optics create halogen-like light and contrast, with the energy and cost-efficient benefits of an LED lamp.

# To learn more about saving money and energy, go to: **gelighting.com/ThinkLED**

When you Think LED lighting, Think GE.



Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions

| PERF   | ORM/         | ANCE [ | DATA          | GE energy smart® LED retail PAR38 lamps |       |               |             |                   |       |                         |     |                                  |                         |                                 |                           |                                |
|--|--------------|--------|---------------|---|-------|---------------|-------------|-------------------|-------|-------------------------|-----|----------------------------------|-------------------------|---------------------------------|---------------------------|--------------------------------|
| BULB<br>SHAPE  | BASE<br>TYPE | WATTS  | ORDER<br>CODE | DESCRIPTION                             | VOLTS | CASE<br>QTY'' | MOL<br>(IN) | LUMENS<br>INITIAL | СВСР  | INTIAL<br>COLOR<br>TEMP | CRI | +RATED<br>LIFE (YRS)<br>3HRS/DAY | *RATED<br>LIFE<br>(HRS) | ^ESTIMATED<br>ENERGY<br>COST/YR | ENERGY<br>STAR®<br>STATUS | ADDITIONAL<br>INFORMATION      |
| Retail Display PAR38 - Non-Dimming (Low Glare - Visual Comfort Lens™)            |              |        |               |   |       |               |             |                   |       |                         |     |                                  |                         |                                 |                           |                                |
| PAR38  | MED          | 14     | 67252         | LED14P38S830/25                         | 120   | 6             | 5.31        | 900               | 4000  | 3000                    | 84  | 22.8                             | 25,000                  | \$1.69                          | $\star$                   | Narrow Flood, 25° Beam, Silver |
|  |              |        | 67253         | LED14P38S830/40                         | 120   | 6             | 5.31        | 900               | 1600  | 3000                    | 84  | 22.8                             | 25,000                  | \$1.69                          | $\star$                   | Flood, 40° Beam, Silver        |
|  |              |        | 67254         | LED14P38S827/25                         | 120   | 6             | 5.31        | 840               | 4000  | 2700                    | 84  | 22.8                             | 25,000                  | \$1.69                          | $\star$                   | Narrow Flood, 25° Beam, Silver |
|  |              |        | 67255         | LED14P38S827/40                         | 120   | 6             | 5.31        | 840               | 1600  | 2700                    | 84  | 22.8                             | 25,000                  | \$1.69                          | *                         | Flood, 40° Beam, Silver        |
| Retail Display PAR38 - Non-Dimming (High CRI - Low Glare - Visual Comfort Lens™) |              |        |               |   |       |               |             |                   |       |                         |     |                                  |                         |                                 |                           |                                |
| PAR38  | MED          | 17     | 61930         | LED17P38S830/15                         | 120   | 6             | 5.31        | 820               | 9000  | 3000                    | 82  | 45.7                             | 50,000                  | \$2.05                          | *                         | Spot, 15° Beam, Silver         |
|  |              |        | 64035         | LED17P38S830/17                         | 120   | 6             | 5.31        | 820               | 7500  | 3000                    | 82  | 45.7                             | 50,000                  | \$2.05                          | $\star$                   | Spot, 17° Beam, Silver         |
|  |              |        | 61931         | LED17P38S830/25                         | 120   | 6             | 5.31        | 820               | 4500  | 3000                    | 87  | 45.7                             | 50,000                  | \$2.05                          | *                         | Narrow Flood, 25° Beam, Silver |
|  |              |        | 65421         | LED17P38S830/40                         | 120   | 6             | 5.31        | 820               | 1550  | 3000                    | 87  | 45.7                             | 50,000                  | \$2.05                          | $\star$                   | Flood, 40° Beam, Silver        |
|  |              |        | 63105         | LED17P38S927/15                         | 120   | 6             | 5.31        | 670               | 7800  | 2700                    | 90  | 45.7                             | 50,000                  | \$2.05                          |                           | Spot, 15° Beam, Silver         |
|  |              |        | 63104         | LED17P38S927/25                         | 120   | 6             | 5.31        | 710               | 3600  | 2700                    | 90  | 45.7                             | 50,000                  | \$2.05                          |                           | Narrow Flood, 25° Beam, Silver |
|  |              |        | 65423         | LED17P38S827/40                         | 120   | 6             | 5.31        | 710               | 1300  | 2700                    | 90  | 45.7                             | 50,000                  | \$2.05                          |                           | Flood, 40° Beam, Silver        |
|  |              | 18     | 68000         | LED18P38S930/15                         | 120   | 6             | 5.31        | 950               | 10600 | 3000                    | 90  | 22.8                             | 25,000                  | \$2.16                          |                           | Spot, 15° Beam, Silver         |
|  |              |        | 68001         | LED18P38S930/25                         | 120   | 6             | 5.31        | 1000              | 5000  | 3000                    | 90  | 22.8                             | 25,000                  | \$2.16                          |                           | Narrow Flood, 25° Beam, Silver |
|  |              |        | 68002         | LED18P38S930/40                         | 120   | 6             | 5.31        | 1000              | 1900  | 3000                    | 90  | 22.8                             | 25,000                  | \$2.16                          |                           | Flood, 40° Beam, Silver        |
|  |              |        | 68003         | LED18P38S927/15                         | 120   | 6             | 5.31        | 900               | 9600  | 2700                    | 92  | 22.8                             | 25,000                  | \$2.16                          |                           | Spot, 15° Beam, Silver         |
|  |              |        | 68004         | LED18P38S927/25                         | 120   | 6             | 5.31        | 950               | 4700  | 2700                    | 92  | 22.8                             | 25,000                  | \$2.16                          |                           | Narrow Flood, 25° Beam, Silver |
|  |              |        | 68005         | LED18P38S927/40                         | 120   | 6             | 5.31        | 950               | 1800  | 2700                    | 92  | 22.8                             | 25,000                  | \$2.16                          |                           | Flood, 40° Beam, Silver        |

For additional product and application information, please consult GE's website: gelighting.com/ThinkLED

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70)

 The life rating is used on the nodes of opened.
 Minimum order quantity = 6
 ENERGY STAR® qualified
 Estimated energy cost per year based on \$0.11 per kWh energy rate and 3 operating hours per day
 Nodes descriptions ending in "TP" indicate a card blister or clamshell package nested in a tra Note: Product descriptions ending in "TP" indicate a card blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

## **ecomagination**™



