PL H 11W BYP TITANIUM LED SERIES 4.0









- Built-in universal voltage driver Bypass installation
- Occupatible with G24d, GX24d, G24d & GX24d bases
- Exceptional efficacy 91 LPW
- Lasts 4 times longer than CFL
- Ompact form factor fits most fixtures
- Available in 3500K, 4000K & 5000K CCT


























PL PRODUCT FEATURES

BYPass Installation

This PL H lamp requires bypassing the ballast during installation and runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




Adiustable Base





This PL H lamp features a base that can be rotated 170° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

PLH 11W BYP TITANIUM LED SERIES 4.0









G24d, GX24d, G24q & GX24q (2/4-pin CFL) Base:

Voltage: 120-277V

Dimmable: No PF: 0.9

Lifetime: 40,000 hrs Weight: 0.27lb / 123g



SPECIFICATIONS*

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
11PLHG4/835/BYP	40816	11	Neutral White 3500K	80	950	86	110°
11PLHG4/840/BYP	40826	11	Natural White 4000K	80	1000	91	110°
11PLHG4/850/BYP	40827	11	Daylight 5000K	80	1000	91	110°

^{*} Specification data is preliminary and may be subject to change
** Suitable for damp locations. Not for use where directly exposed to weather or water
*** Not intended for use in enclosed fixtures
**** Full installation guide and more details available on website