



LED MR16 12V AC/DC Lamp

4.5W 12V AC/DC LED MR16 GU5.3 BASE - 35,000 HOURS (L70) - COB LED

| Nominal Wattage | Overdrive Model # | Description | Initial Lumen | Lm/watt | Beam Angle | CBCP | Average Rated Life(Hrs.) | Dia Inch | Length Inch | Case Qty | Item # |
|-----------------|-------------------|--|---------------|---------|------------|------|--------------------------|----------|-------------|----------|--------|
| 4.5W | L5MR16SW/SP/27K | 4.5W LED MR16 Warm White - 2700K - NFL | 230 | 51 | 20° | 1500 | 35,000 | 1.95" | 1.95" | 48 | 530 |
| 4.5W | L5MR16SW/FL/27K | 4.5W LED MR16 Warm White - 2700K - FL | 215 | 48 | 36° | 400 | 35,000 | 1.95" | 1.95" | 48 | 533 |
| 4.5W | L5MR16SW/SP/30K | 4.5W LED MR16 Warm White - 3000K - NFL | 245 | 54 | 20° | 1700 | 35,000 | 1.95" | 1.95" | 48 | 531 |
| 4.5W | L5MR16SW/FL/30K | 4.5W LED MR16 Warm White - 3000K - FL | 230 | 51 | 36° | 440 | 35,000 | 1.95" | 1.95" | 48 | 534 |
| 4.5W | L5MR16SW/SP/50K | 4.5W LED MR16 Daylight - 5000K - NFL | 275 | 61 | 20° | 1830 | 35,000 | 1.95" | 1.95" | 48 | 532 |
| 4.5W | L5MR16SW/FL/50K | 4.5W LED MR16 Daylight - 5000K - FL | 255 | 57 | 36° | 480 | 35,000 | 1.95" | 1.95" | 48 | 535 |

7W 12V AC/DC LED DIMMABLE MR16 GU5.3 BASE

| Nominal Wattage | Overdrive Model # | Description | Initial Lumen | Lm/watt | Beam Angle | CBCP | Average Rated Life(Hrs.) | Dia Inch | Length Inch | Case Qty | Item # |
|-----------------|-------------------|-------------------------------------|---------------|---------|------------|------|--------------------------|----------|-------------|----------|--------|
| 7W | L7WMR16DIM/FL/30K | 7W LED MR16 Soft White - 3000K - FL | 520 | 74 | 40° | NA | 35,000 | 1.95" | 1.85" | 24 | 595 |
| 7W | L7WMR16DIM/FL/50K | 7W LED MR16 Soft White - 5000K - FL | 560 | 80 | 40° | NA | 35,000 | 1.95" | 1.85" | 24 | 596 |

5W/7W LED DIMMABLE MR16 GU10 BASE - 35,000 HOURS - SMD MID POWER LED

| | | | | | | | | | | | | |
|----|------------------|--------------------------------|-----|----|-----|------|--------|-------|-------|----|-------|-----|
| 5W | L5MRGUDIM/FL/30K | 5W MR16 LED GU10 Flood - 3000K | 380 | 76 | 40° | 750 | 35,000 | 1.97" | 2.17" | 24 | = 35W | 563 |
| 5W | L5MRGUDIM/FL/50K | 5W MR16 LED GU10 Flood - 5000K | 400 | 80 | 40° | 810 | 35,000 | 1.97" | 2.17" | 24 | = 35W | 564 |
| 7W | L7MRGUDIM/FL/30K | 7W MR16 LED GU10 Flood - 3000K | 520 | 74 | 40° | 1050 | 35,000 | 1.97" | 2.17" | 24 | = 50W | 565 |
| 7W | L7MRGUDIM/FL/50K | 7W MR16 LED GU10 Flood - 5000K | 560 | 80 | 40° | 1190 | 35,000 | 1.97" | 2.17" | 24 | = 50W | 566 |

Applications



RECESSED CANS



TRACK LIGHTING

Features

- Designed for long product life - electronics and LEDs
- Instantly bright and color stability over lifetime of product
- Environmentally friendly - mercury free & lead free
- Maintenance free for more than ten years (assuming 8 hours per day 365 days per year)
- Significantly reduces maintenance costs
- Intelligently and aesthetically designed
- Low energy consumption Save up to 90% in energy cost
- Direct replacement and easy to fit
- Instant On Light

Notes

- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance
- Lumen Maintenance (L70 > 35,000 hrs.)
- Specifications can be changed without prior notice, as LED is a dynamic & new evolving technology
- Not suitable for use with dimmers
- Use in dry location only