LITHONIA LIGHTING®

Catalog Number	
Notes	
Type	

FEATURES & SPECIFICATIONS

INTENDED USE — The OLFL provides years of maintenance-free general illumination for residential or commercial outdoor applications such as yards, driveways, patios, loading areas and warehouses.

CONSTRUCTION — Dusk-to-dawn photocell automatically turns on at dusk and off at dawn for convenience and energy savings.

Rugged cast-aluminum, corrosion-resistant housing in bronze finish.

Tempered glass lens is fully gasketed to protect LEDs and keep out moisture, dirt and bugs.

120V driver operates at 60 Hz.

Rated for outdoor installations, -40°C minimum ambient.

OPTICS — High-performance LEDs produce 1400 lumens and maintain 70% of light output at 50,000 hours of service. (LED lifespan based on IESNA LM-80-08 results and calculated per IESNA TM-21-11 methodology.)

Precision optics and reflector for maximum light output.

See Lighting Facts Labels for specific fixture performance.

INSTALLATION — Mounts easily to existing junction box on wall or under eave.

Adjustable head allows precise illumination.

LISTINGS — UL Listed to US and Canadian safety standards for wet locations. ENERGY STAR® certified.

WARRANTY — 5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.

Outdoor General Purpose

OLFL

LED FLOODLIGHT



All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION All configurations of this product are considered "standard" and have short lead times.

Example: OLFL 14 PE BZ

OLFL	14		PE	BZ
Series	**Lumens / Color temperature (CCT)[1]**	**Voltage**	**Control**	**Finish**
OLFL	**14** 1351 lumens / 4000K	**(blank)** 120V	**PE** Button photocell	**BZ** Bronze

Notes

1 Nominal Correlated Color Temperature (CCT) per ANSI C78.377-2008.

PHOTOMETRIC DIAGRAMS

To see complete photometric reports or download .ies files for this product,visit the OLFL home page on www.Lithonia.com. Tested in accordance with IESNA LM-79 and LM-80 standards. Actual wattage may differ by +/- 8% when operating between 120V +/- 10%.

OLFL 14







DECORATIVE INDOOR & OUTDOOR: One Lithonia Way, Conyers, GA 30012 Phone: 800-748-5070 Fax: 770-860-3903 www.lithonia.com © 2013-2014 Acuity Brands Lighting, Inc. All rights reserved. Rev. 08/26/14