



GTL LED Recessed Troffer

LBL LED Wraparound

Step up to LED without breaking the bank!

The Contractor Select® GTL LED recessed troffer and LBL LED surface-mount wraparound from Lithonia Lighting® present two affordable LED options for general-purpose ambient lighting. Built on tried-and-true GT troffer and LB low-profile basket wraparounds, these LED luminaires are priced for the budget-conscious.

LED technology ensures reliable color consistency and extended service life of at least 50,000 hours. Less input watts and no lamp maintenance minimize your total cost of ownership.

- Common appearances to complement existing design applications
- 2'x4' GTL LED replaces 2-lamp T8; 2'x2' GTL LED replaces 2- to 4-lamp T8; and, LBL LED replaces 2-lamp T8
- LED technology with MVOLT (120-277V) driver
- 0-10V Dimming on the GTL LED Troffer
- Multiple lumen packages
- *Best Value in Lighting®*



CONTRACTOR
SELECT



Affordable LED from the company you have relied on for over 65 years. What will you light next?



GTL LED Recessed Troffer

- Available in 2'x2' and 2'x4' configurations, 3700 and 4000 lumens, respectively
- 3500K and 4000K
- 0-10V dimming
- DLC qualified product
- Pattern 12 prismatic lens
- Ideal for grid ceilings

50,000 HOURS | MVOLT | 3700 LUMENS | 43 INPUT WATTS | 3500K TEMP | 4000K TEMP | 82 CRI



LBL LED Surface-Mount Wraparound

- Available in 2' and 4' configurations, 2000 and 4000 lumens, respectively
- 3500K and 4000K
- 4' configuration is a DLC qualified product
- Lift and shift diffuser
- Pattern 12 acrylic with linear side prisms
- Suitable for all surface-mount applications

50,000 HOURS | MVOLT | 2000 LUMENS | 50 INPUT WATTS | 3500K TEMP | 4000K TEMP | 82 CRI

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 2GTL4 LP835

Contractor Select GTL LED Recessed Troffer									
Series	Door	Lens	Voltage	Color Temperature	Options				
2GTL2	2'x2' recessed LED Luminaire Nominal 3700 lumens, 43 input watts ¹ .	(blank) Flush steel, white	(blank) #12 pattern acrylic	(blank) MVOLT (120-277V) 347V 347V	LP835 82 CRI, 3500 Kelvin LP840 82 CRI, 4000 Kelvin				
2GTL4	2'x4' recessed LED Luminaire Nominal 4000 lumens, 43 input watts ¹ .								

Example: LBL2 LP835

Contractor Select LBL LED Wraparound						
Series	Lens	Voltage	Color Temperature	Options		
LBL2	2' surface-mount LED Wraparound Nominal 2000 lumens, 26 input watts ¹ .	(blank) #12 pattern acrylic with linear side prisms	(blank) MVOLT (120-277V) 347V 347V	LP835 82 CRI, 3500 Kelvin LP840 82 CRI, 4000 Kelvin		
LBL4	4' surface-mount LED Wraparound Nominal 4000 lumens, 50 input watts ¹ .					

Notes: ¹ Actual wattage may differ by +/- 5% when operating between 120-277V +/- 10%.

Need more out of your LED luminaire? Don't forget our specification TL Series LED troffer!

NOT QUITE READY FOR LED?

Be sure to check out our competitive fluorescent Contractor Select Lensed Troffers and Curved-Basket Wraps on Lithonia.com.

