



Features

The first Double Ended Horticultural Reflector suitable for both indoor and greenhouse applications. Flexibility within the unit, combined with end user functionality, makes this product one of a kind.

- Patented Concealed Vacuum Airflow Technology maximizes the hood's photometric performance and thermal dissipation
- Includes 4-way, field-selectable 8" removable flanges, solid plates, and louvered plates for fully sealed air-cooled or non air-cooled operations
- Removable 1/8" thick tempered glass door for optional air-cooled or non air-cooled operation

Exceptional housing quality ensures reliability and durability, minimizing down time due to maintenance and cleaning

- Durable powder coated finish
- Constructed of heavy-duty 22 gauge steel
- Removable door for easy lamp access and cleaning
- Re-designed sockets make re-lamping easy
- Standard with 15' cord and ballast plug
- One (1) pair of V-hooks for mounting
- 600-1000w HPS DE standard or high frequency lamps
- UL listed for damp locations

Dimensions: L 17.5" x W 10.5" x H 9.75"
(Add 5" if 8" ducts are used)

Weight: 13.5 lbs / 6.2 kgs
(Glass included)

Weight: 10 lbs / 4.6 kgs
(Open - No Glass)

Item No. GLH-HDE-8
UPC 609728141394



Lamp and ballast not included

Specifications are subject to change without notice