



**Product Number:** 54605

**Order Abbreviation:** HPL 750/120 (UCF)

**General Description:** 750 watt, tungsten halogen, HPL series

#### Product Information

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Abbrev. With Packaging Info.      | HPL750120 (UCF) 120V 12/CS 1/SKU |
| Application                       | Stage & Studio                   |
| Average Rated Life (hr)           | 300                              |
| Base                              | Medium Bipin with Heat Sink      |
| Bulb                              | T6                               |
| Class                             | C (gas)                          |
| Color Rendering Index (CRI)       | 100                              |
| Color Temperature (K)             | 3250                             |
| Diameter d (in)                   | 0.748                            |
| Diameter d (mm)                   | 19.00                            |
| Distance a (in)                   | 2.352                            |
| Distance a (mm)                   | 60.3                             |
| Family Brand Name                 | HPL                              |
| Filament                          | 4-C8                             |
| Length l (in)                     | 4.1                              |
| Length l (mm)                     | 104                              |
| Length l max. (in)                | 4.1                              |
| Length l max. (mm)                | 104                              |
| Light Center Length - LCL (in)    | 2.352                            |
| Light Center Length - LCL (mm)    | 60.3                             |
| Luminous Flux (lm)                | 21900                            |
| Maximum Overall Length - MOL (in) | 4.1                              |
| Maximum Overall Length - MOL (mm) | 104                              |
| Nominal Voltage (V)               | 120.00                           |
| Nominal Wattage (W)               | 750.00                           |
| Operating Position                | Any                              |
| Reflector Coating                 | 19.00                            |
| Type of Current                   | AC                               |

#### Footnotes

- High-performance HPL halogen lamps are manufactured under license from ETC, Inc.