



24V DC Installation Guide

20W - 96W 24V DC Class 2 Voltage LED Drivers (UL Listed)



BEFORE YOU BEGIN

DimmingDimmable with any standard MLV/Incandescent TRIAC (Leading edge) dimmer switches.

This driver is to be installed in accordance with Article 450 of the National Electric Code. The driver must be installed in a well-ventilated area free from explosive gases and vapors. Proper operation requires for free flow of air. As this driver is hardwired it should only be installed by a qualified electrician.

Dimmer switch is to be installed on the input (120VAC side) of the driver.

Precautions Before Installing

Check the label and ensure the driver has the proper input voltage and wattage for the job. Check the wire markings to ensure they match the wiring diagram on this installation guide.

the driver.

Please visit our website for a full dimmer compatibility list.

- www.magnitudeinc.com

Mounting

Select a suitable location capable of supporting the weight of the driver. Use the two keyholes in the driver case. It is recommended that the driver be mounted vertically with the wiring compartment pointing down.

If you need to quickly calculate the drop voltage

Magnigauge - The Ultimate Drop Voltage Calculator **Free App** suitable for Apple and Andriod Devices

Click Here to Download

Or go to www.magnigauge.magnitudeinc.com

Input Connections / Grounding

Remove the wiring compartment knockouts and install the clamp connectors provided with the driver. With power turned off, route the input wires through the clamp connector and connect one wire to black and one wire to white. for all wire connections use only UL listed wire nuts and connectors of suitable size and type. The driver case MUST be grounded in accordance with the N.E.C. Connect the ground wire to the driver green wire.

QUICK SPECS

Input Voltage	120V AC
Output Voltage	24V DC
Operating Temperature	-20°c - 70°c (-4°F - 158°F)
Enclosure	IP67 - Dry and damp location rated
Dimensions (inch)	6.77" x 2.67" x 1.26"
Weight	17 oz

Output Connections

Bring the wires of the light fixture through the other clamp connector and connect them to the driver wires - positive to the red (+) wire and negative to purple (-) wire.

