

MICRO BRITE™

A19 Cold Cathode Fluorescent Lamps



A19

Features and Benefits

- 18,000 to 25,000-hour life
- Up to 85% energy savings
- Dimmable
- Flashable
- Fits standard fixtures
- Reduces replacement and maintenance costs
- Can be used indoors or outdoors
- 2-year warranty

Applications

- General lighting
- Sign applications
- Table lamps
- Architectural perimeter lighting
- Exterior cove and accent lighting

Micro-Brite Dimmable A19 Cold Cathode Fluorescent Lamps

Micro-Brite™ cold cathode fluorescent lamps from Litetronics are a direct replacement for incandescent lighting. Micro-Brite lamps have an expected life of up to 25,000 hours and can save up to 85% in energy costs when compared to incandescent lamps. Due to their extremely long life, Micro-Brite lamps also cut down on maintenance and replacement costs.

The Micro-Brite A19 lamp is the same shape and size as an incandescent A19, but with all the benefits of cold cathode technology. Micro-Brite A19 lamps are available in 3, 5, and 8-watt models to replace 20-watt through 45-watt incandescent lamps. With these immense energy savings, Micro-Brite A19 lamps actually pay for themselves. Micro-Brite A19 lamps are available in a complete line of colors: 2250K, 2700K, 2850K, and 4100K. Switch to Micro-Brite, and start saving money today.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

distributed by:

MICRO BRITE™ Cold Cathode Micro Compact Fluorescent Lamps



A19

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	M.O.L.**
A19	*3 \$	MED	120	3W A19 CL SW	MB-310	15	25,000	82	2700	130	4-1/4"
	5 \$	MED LO	120	5W A19 CL LW	MB-500DL	15	25,000	82	2250	200	4-1/4"
	5 \$	MED LO	120	5W A19 CL PW	MB-500DP	15	25,000	82	2850	200	4-1/4"
	5 \$	MED LO	120	5W A19 WH LW	MB-501DL	15	25,000	82	2250	200	4-1/4"
	5 \$	MED LO	120	5W A19 WH PW	MB-501DP	15	25,000	82	2850	200	4-1/4"
	5 \$	MED	120	5W A19 WH 4	MB-502D	15	25,000	82	4100	200	4-1/4"
	°8 \$	MED LO	120	8W A19 CL LW	MB-800DL	15	18,000	82	2250	325	4-7/8"
	°8 \$	MED LO	120	8W A19 CL PW	MB-800DP	15	18,000	82	2850	325	4-7/8"
	°8 \$	MED LO	120	8W A19 WH LW	MB-801DL	15	18,000	82	2250	325	4-7/8"
	°8 \$	MED LO	120	8W A19 WH PW	MB-801DP	15	18,000	82	2850	325	4-7/8"
	°8 \$	MED	120	8W A19 WH 4	MB-802D	15	18,000	82	4100	325	4-7/8"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
MIN STARTING TEMPERATURE	5°F
MAX OPERATING TEMPERATURE	105°F
POWER FACTOR	> .90
TOTAL HARMONIC DISTORTION	< .30

CONVERSION CHART

CFL	=	INCANDESCENT
3-watt	=	20-watt
5-watt	=	30-watt
8-watt	=	45-watt

§ Energy Savings

* Non-Dimming

° Non-Flashing

** Maximum Overall Length (in inches)

