



T2 SUPER MINI SPIRAL

T2 Super Mini Spiral								
Nominal Wattage	Overdrive Model #	Item Description & CCT	Initial Lumen	Average Rated Life (Hrs.)	Diameter (Inches/mm)	Length/ (Inches/mm)	Pack Inner/ Master	Item #
9	● 9W/ODT2S	9W Super Mini Spiral T2-CFL-Soft White	520	10,000	1.8 / 40	4.0 / 101	25/50	059
9	● 9W/ODT2S/41K	9W Super Mini Spiral T2-CFL-Cool White	520	10,000	1.8 / 40	4.0 / 101	25/50	060
9	● 9W/ODT2S/50K	9W Super Mini Spiral T2-CFL-Natural DL	510	10,000	1.8 / 40	4.0 / 101	25/50	061
13	● 13W/ODT2S	13W Super Mini Spiral T2-CFL-Soft White	825	10,000	1.8 / 46	4.1 / 105	25/50	062
13	● 13W/ODT2S/41K	13W Super Mini Spiral T2-CFL-Cool White	825	10,000	1.8 / 46	4.1 / 105	25/50	063
13	● 13W/ODT2S/50K	13W Super Mini Spiral T2-CFL-Natural DL	825	10,000	1.8 / 46	4.1 / 105	25/50	064
13	● 13W/ODT2S/E12	13W T2 Spiral CFL Candelabra Base Soft White	825	10,000	1.8 / 46	4.2 / 106	25/50	165
13	● 13W/ODT2S/E12/41K	13W T2 Spiral CFL Candelabra Base Cool White	825	10,000	1.8 / 46	4.2 / 106	25/50	171
13	● 13W/ODT2S/E12/50K	13W T2 Spiral CFL Candelabra Base Natural DL	825	10,000	1.8 / 46	4.2 / 106	25/50	172
18	● 18W/ODT2S	18W Super Mini Spiral T2-CFL-Soft White	1,100	10,000	2.1 / 54	4.5 / 115	25/50	065
18	● 18W/ODT2S/41K	18W Super Mini Spiral T2-CFL-Cool White	1,200	10,000	2.1 / 54	4.5 / 115	25/50	066
18	● 18W/ODT2S/50K	18W Super Mini Spiral T2-CFL-Natural DL	1,200	10,000	2.1 / 54	4.5 / 115	25/50	067
23	● 23W/ODT2S	23W Super Mini Spiral T2-CFL-Soft White	1,600	10,000	2.1 / 54	4.9 / 124	25/50	068
23	● 23W/ODT2S/27K	23W Super Mini Spiral T2-CFL-Warm White	1,600	10,000	2.1 / 54	4.9 / 124	25/50	069
23	● 23W/ODT2S/41K	23W Super Mini Spiral T2-CFL-Cool White	1,600	10,000	2.1 / 54	4.9 / 124	25/50	070
23	● 23W/ODT2S/50K	23W Super Mini Spiral T2-CFL-Natural DL	1,600	10,000	2.1 / 54	4.9 / 124	25/50	117
26	● 26W/ODT2S	26W Super Mini Spiral T2-CFL-Soft White	1,750	10,000	2.1 / 54	5.1 / 129	25/50	120
26	● 26W/ODT2S/41K	26W Super Mini Spiral T2-CFL-Cool White	1,750	10,000	2.1 / 54	5.1 / 129	25/50	121
26	● 26W/ODT2S/50K	26W Super Mini Spiral T2-CFL-Natural DL	1,750	10,000	2.1 / 54	5.1 / 129	25/50	121

Applications



WALL SCENE CEILING TABLE/ FLOOR LAMPS READING LAMP OUTDOOR COVERED

Features

- 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact size- Fits most applications

Notes

- Not Dimmable
- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance

